JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.file

Class InvalidPathException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalArgumentException
          java.nio.file.InvalidPathException

All Implemented Interfaces:

Serializable

```
public class InvalidPathException
extends IllegalArgumentException
```

Unchecked exception thrown when path string cannot be converted into a Path because the path string contains invalid characters, or the path string is invalid for other file system specific reasons.

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`InvalidPathException(String input, String reason)`	Constructs an instance from the given input

	string and reason.
`InvalidPathException(String input, String reason, int index)`	Constructs an instance from the given input string, reason, and error index.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`int`	`getIndex()`	Returns an index into the input string of the position at which the error occurred, or -1 if this position is not known.
`String`	`getInput()`	Returns the input string.
`String`	`getMessage()`	Returns a string describing the error.
`String`	`getReason()`	Returns a string explaining why the input string was rejected.

Methods inherited from class java.lang.Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Detail

InvalidPathException

```
public InvalidPathException(String input,
                            String reason,
                            int index)
```

Constructs an instance from the given input string, reason, and error index.

Parameters:

`input` - the input string

`reason` - a string explaining why the input was rejected

`index` - the index at which the error occurred, or -1 if the index is not known

Throws:

`NullPointerException` - if either the input or reason strings are null

`IllegalArgumentException` - if the error index is less than -1

InvalidPathException

```
public InvalidPathException(String input,
                            String reason)
```

Constructs an instance from the given input string and reason. The resulting object will have an error index of -1.

Parameters:

`input` - the input string

`reason` - a string explaining why the input was rejected

Throws:

`NullPointerException` - if either the input or reason strings are null

Method Detail

getInput

```
public String getInput()
```

Returns the input string.

Returns:

the input string

getReason

```
public String getReason()
```

Returns a string explaining why the input string was rejected.

Returns:

the reason string

getIndex

```
public int getIndex()
```

Returns an index into the input string of the position at which the error occurred, or `-1` if this position is not known.

Returns:

the error index

getMessage

```
public String getMessage()
```

Returns a string describing the error. The resulting string consists of the reason string followed by a colon character (`':'`), a space, and the input string. If the error index is defined then the string `" at index "` followed by the index, in decimal, is inserted after the reason string and before the colon character.

Overrides:

`getMessage` in class `Throwable`

Returns:

```
a string describing the error
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.