JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.file.attribute

Class AclEntry

java.lang.Object
    java.nio.file.attribute.AclEntry

```
public final class AclEntry
extends Object
```

An entry in an access control list (ACL).

The ACL entry represented by this class is based on the ACL model specified in *RFC 3530: Network File System (NFS) version 4 Protocol*. Each entry has four components as follows:

1. The `type` component determines if the entry grants or denies access.
2. The `principal` component, sometimes called the "who" component, is a `UserPrincipal` corresponding to the identity that the entry grants or denies access
3. The `permissions` component is a set of `permissions`
4. The `flags` component is a set of `flags` to indicate how entries are inherited and propagated

ACL entries are created using an associated `AclEntry.Builder` object by invoking its `build` method.

ACL entries are immutable and are safe for use by multiple concurrent threads.

Since:

1.7

Nested Class Summary

Nested Classes

Modifier and Type	Class	Description
static class	AclEntry.Builder	A builder of AclEntry objects.

Method Summary

Instance Methods | **Concrete Methods**

Modifier and Type	Method	Description
boolean	equals(Object ob)	Compares the specified object with this ACL entry for equality.
Set<AclEntryFlag>	flags()	Returns a copy of the flags component.
int	hashCode()	Returns the hash-code value for this ACL entry.
static AclEntry.Builder	newBuilder()	Constructs a new builder.
static AclEntry.Builder	newBuilder(AclEntry entry)	Constructs a new builder with the components of an existing ACL entry.
Set<AclEntryPermission>	permissions()	Returns a copy of the permissions component.

UserPrincipal	principal()	Returns the principal component.
String	toString()	Returns the string representation of this ACL entry.
AclEntryType	type()	Returns the ACL entry type.

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Method Detail

newBuilder

```
public static AclEntry.Builder newBuilder()
```

Constructs
a new builder. The initial value of the type and who components is `null`. The initial value of the permissions and flags components is the empty set.

Returns:

a new builder

newBuilder

```
public static AclEntry.Builder newBuilder(AclEntry entry)
```

Constructs a new builder with the components of an existing ACL entry.

Parameters:

entry - an ACL entry

Returns:

a new builder

type

```
public AclEntryType type()
```

Returns the ACL entry type.

Returns:

the ACL entry type

principal

```
public UserPrincipal principal()
```

Returns the principal component.

Returns:

the principal component

permissions

```
public Set<AclEntryPermission> permissions()
```

Returns a copy of the permissions component.

The returned set is a modifiable copy of the permissions.

Returns:

the permissions component

flags

```
public Set<AclEntryFlag> flags()
```

Returns a copy of the flags component.

The returned set is a modifiable copy of the flags.

Returns:

the flags component

equals

```
public boolean equals(Object ob)
```

Compares the specified object with this ACL entry for equality.

If the given object is not an `AclEntry` then this method immediately returns `false`.

For two ACL entries to be considered equals requires that they are both the same type, their who components are equal, their permissions components are equal, and their flags components are equal.

This method satisfies the general contract of the `Object.equals` method.

Overrides:

`equals` in class `Object`

Parameters:

`ob - the object to which this object is to be compared`

Returns:

`true if, and only if, the given object is an AclEntry that is identical to this AclEntry`

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

Returns the hash-code value for this ACL entry.

This method satisfies the general contract of the `Object.hashCode()` method.

Overrides:

`hashCode` in class `Object`

Returns:

`a hash code value for this object.`

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

toString

```
public String toString()
```

Returns the string representation of this ACL entry.

Overrides:

`toString` in class `Object`

Returns:

```
the string representation of this entry
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.