JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.file.attribute

Interface BasicFileAttributeView

All Superinterfaces:

`AttributeView`, `FileAttributeView`

All Known Subinterfaces:

`DosFileAttributeView`, `PosixFileAttributeView`

```
public interface BasicFileAttributeView
extends FileAttributeView
```

A file attribute view that provides a view of a *basic set* of file attributes common to many file systems. The basic set of file attributes consist of *mandatory* and *optional* file attributes as defined by the `BasicFileAttributes` interface.

The file attributes are retrieved from the file system as a *bulk operation* by invoking the `readAttributes` method. This class also defines the `setTimes` method to update the file's time attributes.

Where dynamic access to file attributes is required, the attributes supported by this attribute view have the following names and types:

Name	Type
"lastModifiedTime"	`FileTime`
"lastAccessTime"	`FileTime`
"creationTime"	`FileTime`
"size"	`Long`
"isRegularFile"	`Boolean`
"isDirectory"	`Boolean`
"isSymbolicLink"	`Boolean`
"isOther"	`Boolean`

"fileKey" Object

The `getAttribute` method may be used to read any of these attributes as if by invoking the `readAttributes()` method.

The `setAttribute` method may be used to update the file's last modified time, last access time or create time attributes as if by invoking the `setTimes` method.

Since:

1.7

Method Summary

Abstract Methods

Modifier and Type	Method	Description
`String`	`name()`	Returns the name of the attribute view.
`BasicFileAttributes`	`readAttributes()`	Reads the basic file attributes as a bulk operation.
`void`	`setTimes(FileTime lastModifiedTime, FileTime lastAccessTime, FileTime createTime)`	Updates any or all of the file's last modified time, last access time, and create time attributes.

Method Detail

name

`String name()`

Returns the name of the attribute view. Attribute views of this type have the name "basic".

Specified by:

name in interface AttributeView

Returns:

the name of the attribute view

readAttributes

```
BasicFileAttributes readAttributes()
                            throws IOException
```

Reads the basic file attributes as a bulk operation.

It is implementation specific if all file attributes are read as an atomic operation with respect to other file system operations.

Returns:

the file attributes

Throws:

IOException - if an I/O error occurs

SecurityException - In the case of the default provider, a security manager is installed, its checkRead method is invoked to check read access to the file

setTimes

```
void setTimes(FileTime lastModifiedTime,
              FileTime lastAccessTime,
              FileTime createTime)
       throws IOException
```

Updates any or all of the file's last modified time, last access time, and create time attributes.

This method updates the file's timestamp attributes. The values are converted to the epoch and precision supported by the file system. Converting from finer to coarser granularities result in precision loss. The behavior of this method when attempting to set a timestamp that is not supported or to a value that is outside the range supported by the underlying file store is not defined. It may or not fail by throwing an IOException.

If any of the lastModifiedTime, lastAccessTime, or createTime parameters has the value null then the corresponding timestamp is not changed. An implementation may require to read the existing values of the file attributes

when only some, but not all, of the timestamp attributes are updated. Consequently, this method may not be an atomic operation with respect to other file system operations. Reading and re-writing existing values may also result in precision loss. If all of the `lastModifiedTime`, `lastAccessTime` and `createTime` parameters are `null` then this method has no effect.

Usage Example: Suppose we want to change a file's last access time.

```
Path path = ...
FileTime time = ...
Files.getFileAttributeView(path, BasicFileAttributeView.class).setTimes(null,
```

Parameters:

`lastModifiedTime` - the new last modified time, or null to not change the value

`lastAccessTime` - the last access time, or null to not change the value

`createTime` - the file's create time, or null to not change the value

Throws:

`IOException` - if an I/O error occurs

`SecurityException` - In the case of the default provider, a security manager is installed, its `checkWrite` method is invoked to check write access to the file

See Also:

`Files.setLastModifiedTime(java.nio.file.Path, java.nio.file.attribute.FileTime)`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.