JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.file.attribute

Enum PosixFilePermission

java.lang.Object
    java.lang.Enum<PosixFilePermission>
        java.nio.file.attribute.PosixFilePermission

All Implemented Interfaces:

Serializable, Comparable<PosixFilePermission>

```
public enum PosixFilePermission
extends Enum<PosixFilePermission>
```

Defines the bits for use with the `permissions` attribute.

The `PosixFilePermissions` class defines methods for manipulating set of permissions.

Since:

1.7

Enum Constant Summary

Enum Constants

Enum Constant	Description
GROUP_EXECUTE	Execute/search permission, group.
GROUP_READ	Read permission, group.
GROUP_WRITE	Write permission, group.
OTHERS_EXECUTE	Execute/search permission, others.
OTHERS_READ	Read permission, others.

OTHERS_WRITE	Write permission, others.
OWNER_EXECUTE	Execute/search permission, owner.
OWNER_READ	Read permission, owner.
OWNER_WRITE	Write permission, owner.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
static **PosixFilePermission**	**valueOf**(**String** name)	Returns the enum constant of this type with the specified name.
static **PosixFilePermission**[]	**values**()	Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

clone, compareTo, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Enum Constant Detail

OWNER_READ

```
public static final PosixFilePermission OWNER_READ
```

Read permission, owner.

OWNER_WRITE

```
public static final PosixFilePermission OWNER_WRITE
```

Write permission, owner.

OWNER_EXECUTE

```
public static final PosixFilePermission OWNER_EXECUTE
```

Execute/search permission, owner.

GROUP_READ

```
public static final PosixFilePermission GROUP_READ
```

Read permission, group.

GROUP_WRITE

```
public static final PosixFilePermission GROUP_WRITE
```

Write permission, group.

GROUP_EXECUTE

```
public static final PosixFilePermission GROUP_EXECUTE
```

Execute/search permission, group.

OTHERS_READ

```
public static final PosixFilePermission OTHERS_READ
```

Read permission, others.

OTHERS_WRITE

```
public static final PosixFilePermission OTHERS_WRITE
```

Write permission, others.

OTHERS_EXECUTE

```
public static final PosixFilePermission OTHERS_EXECUTE
```

Execute/search permission, others.

Method Detail

values

```
public static PosixFilePermission[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (PosixFilePermission c : PosixFilePermission.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static PosixFilePermission valueOf(String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

IllegalArgumentException - if this enum type has no constant with the specified name

NullPointerException - if the argument is null

C

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.