JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.file.attribute

Class PosixFilePermissions

java.lang.Object
    java.nio.file.attribute.PosixFilePermissions

```
public final class PosixFilePermissions
extends Object
```

This class consists exclusively of static methods that operate on sets of `PosixFilePermission` objects.

Since:

1.7

Method Summary

Concrete Methods

Modifier and Type	Method
static `FileAttribute<Set<PosixFilePermission>>`	`asFileAttribute(Set<PosixFilePerm`
static `Set<PosixFilePermission>`	`fromString(String perms)`

static **String**	**toString**(**Set**<**PosixFilePermission**>

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

toString

```
public static String toString(Set<PosixFilePermission> perms)
```

Returns the `String` representation of a set of permissions. It is guaranteed that the returned `String` can be parsed by the `fromString(java.lang.String)` method.

If the set contains `null` or elements that are not of type `PosixFilePermission` then these elements are ignored.

Parameters:

`perms - the set of permissions`

Returns:

`the string representation of the permission set`

fromString

```
public static Set<PosixFilePermission> fromString(String perms)
```

Returns the set of permissions corresponding to a given `String` representation.

The `perms` parameter is a `String` representing the permissions. It has 9 characters that are interpreted as three sets of three. The first set refers to the owner's permissions; the next to the group permissions and the last to others. Within each set, the first character is `'r'` to indicate permission to read, the second character is `'w'` to indicate permission to write, and the

third character is `'x'` for execute permission. Where a permission is not set then the corresponding character is set to `'-'`.

Usage Example: Suppose we require the set of permissions that indicate the owner has read, write, and execute permissions, the group has read and execute permissions and others have none.

```
Set<PosixFilePermission> perms = PosixFilePermissions.fromString("rwxr-x---");
```

Parameters:

`perms - string representing a set of permissions`

Returns:

`the resulting set of permissions`

Throws:

`IllegalArgumentException - if the string cannot be converted to a set of permissions`

See Also:

`toString(Set)`

asFileAttribute

```
public static FileAttribute<Set<PosixFilePermission>> asFileAttribute(Set<PosixFi
```

Creates a `FileAttribute`, encapsulating a copy of the given file permissions, suitable for passing to the `createFile` or `createDirectory` methods.

Parameters:

`perms - the set of permissions`

Returns:

`an attribute encapsulating the given file permissions with name "posix:permissions"`

Throws:

ClassCastException - if the set contains elements that are not of type PosixFilePermission

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.