JavaScript is disabled on your browser.

compact1, compact2, compact3

java.nio.file.attribute

Interface UserPrincipal

All Superinterfaces:

`Principal`

All Known Subinterfaces:

`GroupPrincipal`

```
public interface UserPrincipal
extends Principal
```

A `Principal` representing an identity used to determine access rights to objects in a file system.

On many platforms and file systems an entity requires appropriate access rights or permissions in order to access objects in a file system. The access rights are generally performed by checking the identity of the entity. For example, on implementations that use Access Control Lists (ACLs) to enforce privilege separation then a file in the file system may have an associated ACL that determines the access rights of identities specified in the ACL.

A `UserPrincipal` object is an abstract representation of an identity. It has a `name` that is typically the username or account name that it represents. User principal objects may be obtained using a `UserPrincipalLookupService`, or returned by `FileAttributeView` implementations that provide access to identity related attributes. For example, the `AclFileAttributeView` and `PosixFileAttributeView` provide access to a file's `owner`.

Since:

1.7

Method Summary

Methods inherited from interface java.security.Principal

`equals, getName, hashCode, implies, toString`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.