JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text

Class AttributedCharacterIterator.Attribute

java.lang.Object
    java.text.AttributedCharacterIterator.Attribute

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

Format.Field, TextAttribute

Enclosing interface:

AttributedCharacterIterator

```
public static class AttributedCharacterIterator.Attribute
extends Object
implements Serializable
```

Defines attribute keys that are used to identify text attributes. These keys are used in `AttributedCharacterIterator` and `AttributedString`.

Since:

1.2

See Also:

AttributedCharacterIterator, AttributedString, Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
static AttributedCharacterIterator.Attribute	INPUT_METHOD_SEGMENT	

		Attribute key for input method segments.
static AttributedCharacterIterator.Attribute	LANGUAGE	Attribute key for the language of some text.
static AttributedCharacterIterator.Attribute	READING	Attribute key for the reading of some text.

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	Attribute(String name)	Constructs an Attribute with the given name.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
boolean	equals(Object obj)	Compares two objects for equality.
protected String	getName()	Returns the name of the attribute.
int	hashCode()	Returns a hash code value for the object.
protected Object	readResolve()	Resolves instances being deserialized to the predefined constants.

String	toString()	Returns a string representation of the object.

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

LANGUAGE

```
public static final AttributedCharacterIterator.Attribute LANGUAGE
```

Attribute key for the language of some text.

Values are instances of Locale.

See Also:

Locale

READING

```
public static final AttributedCharacterIterator.Attribute READING
```

Attribute key for the reading of some text. In languages where the written form and the pronunciation of a word are only loosely related (such as Japanese), it is often necessary to store the reading (pronunciation) along with the written form.

Values are instances of Annotation holding instances of String.

See Also:

Annotation, String

INPUT_METHOD_SEGMENT

```
public static final AttributedCharacterIterator.Attribute INPUT_METHOD_SEGMENT
```

Attribute key for input method segments. Input methods often break up text into segments, which usually correspond to words.

Values are instances of `Annotation` holding a `null` reference.

See Also:

`Annotation`

Constructor Detail

Attribute

```
protected Attribute(String name)
```

Constructs an `Attribute` with the given name.

Parameters:

`name - the name of Attribute`

Method Detail

equals

```
public final boolean equals(Object obj)
```

Compares two objects for equality. This version only returns true for `x.equals(y)` if `x` and `y` refer to the same object, and guarantees this for all subclasses.

Overrides:

`equals` in class `Object`

Parameters:

`obj - the reference object with which to compare.`

Returns:

`true if this object is the same as the obj argument; false otherwise.`

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public final int hashCode()
```

Returns a hash code value for the object. This version is identical to the one in `Object`, but is also final.

Overrides:

`hashCode` in class `Object`

Returns:

`a hash code value for this object.`

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

toString

```
public String toString()
```

Returns a string representation of the object. This version returns the concatenation of class name, `"("`, a name identifying the attribute and `")"`.

Overrides:

`toString` in class `Object`

Returns:

a string representation of the object.

getName

```
protected String getName()
```

Returns the name of the attribute.

Returns:

the name of Attribute

readResolve

```
protected Object readResolve()
                     throws InvalidObjectException
```

Resolves instances being deserialized to the predefined constants.

Returns:

the resolved Attribute object

Throws:

InvalidObjectException - if the object to resolve is not an instance of Attribute

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.