JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text

Interface AttributedCharacterIterator

All Superinterfaces:

`CharacterIterator`, `Cloneable`

```
public interface AttributedCharacterIterator
extends CharacterIterator
```

An `AttributedCharacterIterator` allows iteration through both text and related attribute information.

An attribute is a key/value pair, identified by the key. No two attributes on a given character can have the same key.

The values for an attribute are immutable, or must not be mutated by clients or storage. They are always passed by reference, and not cloned.

A *run with respect to an attribute* is a maximum text range for which:

- the attribute is undefined or `null` for the entire range, or
- the attribute value is defined and has the same non-`null` value for the entire range.

A *run with respect to a set of attributes* is a maximum text range for which this condition is met for each member attribute.

When getting a run with no explicit attributes specified (i.e., calling `getRunStart()` and `getRunLimit()`), any contiguous text segments having the same attributes (the same set of attribute/value pairs) are treated as separate runs if the attributes have been given to those text segments separately.

The returned indexes are limited to the range of the iterator.

The returned attribute information is limited to runs that contain the current character.

Attribute keys are instances of `AttributedCharacterIterator.Attribute` and its subclasses, such as `TextAttribute`.

Since:

1.2

See Also:

`AttributedCharacterIterator.Attribute`, `TextAttribute`, `AttributedString`, `Annotation`

Nested Class Summary

Nested Classes

Modifier and Type	Interface	Description
static class	**AttributedCharacterIterator.Attribute**	Defines attribute keys that are used to identify text attributes.

Field Summary

Fields inherited from interface java.text.CharacterIterator

`DONE`

Method Summary

Abstract Methods

Modifier and Type	Method
Set<AttributedCharacterIterator.Attribute>	**getAllAttributeKeys()**
Object	**getAttribute(AttributedCharact**

Map<AttributedCharacterIterator.Attribute,Object>	getAttributes()
int	getRunLimit()
int	getRunLimit(AttributedCharacte
int	getRunLimit(Set<? extends AttributedCharacterIterator.At

int	**getRunStart**()
int	**getRunStart**(**AttributedCharacte**
int	**getRunStart**(**Set**<? extends **AttributedCharacterIterator.At**

Methods inherited from interface java.text.CharacterIterator

clone, current, first, getBeginIndex, getEndIndex, getIndex, last, next, previous, setIndex

Method Detail

getRunStart

```
int getRunStart()
```

Returns the index of the first character of the run with respect to all attributes containing the current character.

Any contiguous text segments having the same attributes (the same set of attribute/value pairs) are treated as separate runs if the attributes have been given to those text segments separately.

Returns:

the index of the first character of the run

getRunStart

```
int getRunStart(AttributedCharacterIterator.Attribute attribute)
```

Returns the index of the first character of the run with respect to the given `attribute` containing the current character.

Parameters:

`attribute` - the desired attribute.

Returns:

the index of the first character of the run

getRunStart

```
int getRunStart(Set<? extends AttributedCharacterIterator.Attribute> attributes)
```

Returns the index of the first character of the run with respect to the given `attributes` containing the current character.

Parameters:

`attributes - a set of the desired attributes.`

Returns:

`the index of the first character of the run`

getRunLimit

```
int getRunLimit()
```

Returns the index of the first character following the run with respect to all attributes containing the current character.

Any contiguous text segments having the same attributes (the same set of attribute/value pairs) are treated as separate runs if the attributes have been given to those text segments separately.

Returns:

`the index of the first character following the run`

getRunLimit

```
int getRunLimit(AttributedCharacterIterator.Attribute attribute)
```

Returns the index of the first character following the run with respect to the given `attribute` containing the current character.

Parameters:

`attribute - the desired attribute`

Returns:

`the index of the first character following the run`

getRunLimit

```
int getRunLimit(Set<? extends AttributedCharacterIterator.Attribute> attributes)
```

Returns the index of the first character following the run with respect to the given `attributes` containing the current character.

Parameters:

`attributes - a set of the desired attributes`

Returns:

`the index of the first character following the run`

getAttributes

`Map<AttributedCharacterIterator.Attribute,Object> getAttributes()`

Returns a map with the attributes defined on the current character.

Returns:

`a map with the attributes defined on the current character`

getAttribute

`Object getAttribute(AttributedCharacterIterator.Attribute attribute)`

Returns the value of the named `attribute` for the current character. Returns `null` if the `attribute` is not defined.

Parameters:

`attribute - the desired attribute`

Returns:

`the value of the named attribute or null`

getAllAttributeKeys

`Set<AttributedCharacterIterator.Attribute> getAllAttributeKeys()`

Returns the keys of all attributes defined on the iterator's text range. The set is empty if no attributes are defined.

Returns:

```
the keys of all attributes
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.