JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text

Class DateFormat.Field

java.lang.Object
  java.text.AttributedCharacterIterator.Attribute
    java.text.Format.Field
      java.text.DateFormat.Field

All Implemented Interfaces:

Serializable

Enclosing class:

DateFormat

```
public static class DateFormat.Field
extends Format.Field
```

Defines constants that are used as attribute keys in the `AttributedCharacterIterator` returned from `DateFormat.formatToCharacterIterator` and as field identifiers in `FieldPosition`.

The class also provides two methods to map between its constants and the corresponding Calendar constants.

Since:

1.4

See Also:

`Calendar`, `Serialized Form`

Field Summary

Fields

Modifier and Type	Field	Description
static DateFormat.Field	AM_PM	Constant identifying the time of day indicator (e.g.
static DateFormat.Field	DAY_OF_MONTH	Constant identifying the day of month field.
static DateFormat.Field	DAY_OF_WEEK	Constant identifying the day of week field.
static DateFormat.Field	DAY_OF_WEEK_IN_MONTH	Constant identifying the day of week field.
static DateFormat.Field	DAY_OF_YEAR	Constant identifying the day of year field.
static DateFormat.Field	ERA	Constant identifying the era field.
static DateFormat.Field	HOUR_OF_DAY0	Constant identifying the hour of day field, where the legal values are 0 to 23.
static DateFormat.Field	HOUR_OF_DAY1	Constant identifying the hour of day field, where the legal values are 1 to 24.
static DateFormat.Field	HOUR0	Constant identifying the hour field, where the legal values are 0 to 11.
static DateFormat.Field	HOUR1	Constant identifying the hour field, where the legal values are 1 to 12.
static DateFormat.Field	MILLISECOND	Constant identifying the millisecond field.
static DateFormat.Field	MINUTE	Constant identifying the minute field.

static DateFormat.Field	MONTH	Constant identifying the month field.
static DateFormat.Field	SECOND	Constant identifying the second field.
static DateFormat.Field	TIME_ZONE	Constant identifying the time zone field.
static DateFormat.Field	WEEK_OF_MONTH	Constant identifying the week of month field.
static DateFormat.Field	WEEK_OF_YEAR	Constant identifying the week of year field.
static DateFormat.Field	YEAR	Constant identifying the year field.

Fields inherited from class java.text.AttributedCharacterIterator.Attribute

INPUT_METHOD_SEGMENT, LANGUAGE, READING

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	Field(String name, int calendarField)	Creates a Field.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
int	getCalendarField()	Returns the Calendar field associated with this attribute.
static DateFormat.Field	ofCalendarField(int calendarField)	Returns the Field constant

		that corresponds to the `Calendar` constant `calendarField`.
protected **Object**	**readResolve**()	Resolves instances being deserialized to the predefined constants.

Methods inherited from class java.text.AttributedCharacterIterator.Attribute

equals, getName, hashCode, toString

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

ERA

```
public static final DateFormat.Field ERA
```

Constant identifying the era field.

YEAR

```
public static final DateFormat.Field YEAR
```

Constant identifying the year field.

MONTH

```
public static final DateFormat.Field MONTH
```

Constant identifying the month field.

DAY_OF_MONTH

```
public static final DateFormat.Field DAY_OF_MONTH
```

Constant identifying the day of month field.

HOUR_OF_DAY1

```
public static final DateFormat.Field HOUR_OF_DAY1
```

Constant identifying the hour of day field, where the legal values are 1 to 24.

HOUR_OF_DAY0

```
public static final DateFormat.Field HOUR_OF_DAY0
```

Constant identifying the hour of day field, where the legal values are 0 to 23.

MINUTE

```
public static final DateFormat.Field MINUTE
```

Constant identifying the minute field.

SECOND

```
public static final DateFormat.Field SECOND
```

Constant identifying the second field.

MILLISECOND

```
public static final DateFormat.Field MILLISECOND
```

Constant identifying the millisecond field.

DAY_OF_WEEK

```
public static final DateFormat.Field DAY_OF_WEEK
```

Constant identifying the day of week field.

DAY_OF_YEAR

```
public static final DateFormat.Field DAY_OF_YEAR
```

Constant identifying the day of year field.

DAY_OF_WEEK_IN_MONTH

```
public static final DateFormat.Field DAY_OF_WEEK_IN_MONTH
```

Constant identifying the day of week field.

WEEK_OF_YEAR

```
public static final DateFormat.Field WEEK_OF_YEAR
```

Constant identifying the week of year field.

WEEK_OF_MONTH

```
public static final DateFormat.Field WEEK_OF_MONTH
```

Constant identifying the week of month field.

AM_PM

```
public static final DateFormat.Field AM_PM
```

Constant identifying the time of day indicator (e.g. "a.m." or "p.m.") field.

HOUR1

```
public static final DateFormat.Field HOUR1
```

Constant identifying the hour field, where the legal values are 1 to 12.

HOUR0

```
public static final DateFormat.Field HOUR0
```

Constant identifying the hour field, where the legal values are 0 to 11.

TIME_ZONE

```
public static final DateFormat.Field TIME_ZONE
```

Constant identifying the time zone field.

Constructor Detail

Field

```
protected Field(String name,
                int calendarField)
```

Creates a `Field`.

Parameters:

`name - the name of the Field`

`calendarField - the Calendar constant this Field corresponds to; any value, even one outside the range of legal Calendar values may be used, but -1 should be used for values that don't correspond to legal Calendar values`

Method Detail

ofCalendarField

```
public static DateFormat.Field ofCalendarField(int calendarField)
```

Returns the `Field` constant that corresponds to the `Calendar` constant `calendarField`. If there is no direct mapping between the `Calendar` constant and a `Field`, null is returned.

Parameters:

`calendarField - Calendar field constant`

Returns:

`Field instance representing calendarField.`

Throws:

`IllegalArgumentException - if calendarField is not the value of a Calendar field constant.`

See Also:

`Calendar`

getCalendarField

```
public int getCalendarField()
```

Returns the `Calendar` field associated with this attribute. For example, if this represents the hours field of a `Calendar`, this would return `Calendar.HOUR`. If there is no corresponding `Calendar` constant, this will return -1.

Returns:

`Calendar constant for this field`

See Also:

`Calendar`

readResolve

```
protected Object readResolve()
                     throws InvalidObjectException
```

Resolves instances being deserialized to the predefined constants.

Overrides:

`readResolve in class AttributedCharacterIterator.Attribute`

Returns:

`resolved DateFormat.Field constant`

Throws:

`InvalidObjectException` - if the constant could not be resolved.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.