JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text

Class FieldPosition

java.lang.Object
    java.text.FieldPosition

```
public class FieldPosition
extends Object
```

`FieldPosition` is a simple class used by `Format` and its subclasses to identify fields in formatted output. Fields can be identified in two ways:

- By an integer constant, whose names typically end with `_FIELD`. The constants are defined in the various subclasses of `Format`.
- By a `Format.Field` constant, see `ERA_FIELD` and its friends in `DateFormat` for an example.

`FieldPosition` keeps track of the position of the field within the formatted output with two indices: the index of the first character of the field and the index of the last character of the field.

One version of the `format` method in the various `Format` classes requires a `FieldPosition` object as an argument. You use this `format` method to perform partial formatting or to get information about the formatted output (such as the position of a field).

If you are interested in the positions of all attributes in the formatted string use the `Format` method `formatToCharacterIterator`.

See Also:

`Format`

Constructor Summary

Constructors

Constructor	Description
`FieldPosition(Format.Field attribute)`	Creates a FieldPosition object for the given field constant.
`FieldPosition(Format.Field attribute, int fieldID)`	Creates a `FieldPosition` object for the given field.
`FieldPosition(int field)`	Creates a FieldPosition object for the given field.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`boolean`	`equals(Object obj)`	Overrides equals
`int`	`getBeginIndex()`	Retrieves the index of the first character in the requested field.
`int`	`getEndIndex()`	Retrieves the index of the character following the last character in the requested field.
`int`	`getField()`	Retrieves the field identifier.
`Format.Field`	`getFieldAttribute()`	Returns the field identifier as an attribute constant from one of the `Field` subclasses.
`int`	`hashCode()`	Returns a hash code for this FieldPosition.
`void`	`setBeginIndex(int bi)`	Sets the begin index.
`void`	`setEndIndex(int ei)`	Sets the end index.

String	toString()	Return a string representation of this FieldPosition.

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Constructor Detail

FieldPosition

```
public FieldPosition(int field)
```

Creates a FieldPosition object for the given field. Fields are identified by constants, whose names typically end with _FIELD, in the various subclasses of Format.

Parameters:

field - the field identifier

See Also:

NumberFormat.INTEGER_FIELD, NumberFormat.FRACTION_FIELD, DateFormat.YEAR_FIELD, DateFormat.MONTH_FIELD

FieldPosition

```
public FieldPosition(Format.Field attribute)
```

Creates a FieldPosition object for the given field constant. Fields are identified by constants defined in the various Format subclasses. This is equivalent to calling new FieldPosition(attribute, -1).

Parameters:

attribute - Format.Field constant identifying a field

Since:

1.4

FieldPosition

```
public FieldPosition(Format.Field attribute,
                     int fieldID)
```

Creates a `FieldPosition` object for the given field. The field is identified by an attribute constant from one of the `Field` subclasses as well as an integer field ID defined by the `Format` subclasses. `Format` subclasses that are aware of `Field` should give precedence to `attribute` and ignore `fieldID` if `attribute` is not null. However, older `Format` subclasses may not be aware of `Field` and rely on `fieldID`. If the field has no corresponding integer constant, `fieldID` should be -1.

Parameters:

`attribute - Format.Field constant identifying a field`

`fieldID - integer constant identifying a field`

Since:

`1.4`

Method Detail

getFieldAttribute

`public Format.Field getFieldAttribute()`

Returns the field identifier as an attribute constant from one of the `Field` subclasses. May return null if the field is specified only by an integer field ID.

Returns:

`Identifier for the field`

Since:

`1.4`

getField

`public int getField()`

Retrieves the field identifier.

Returns:

`the field identifier`

getBeginIndex

`public int getBeginIndex()`

Retrieves the index of the first character in the requested field.

Returns:

the begin index

getEndIndex

```
public int getEndIndex()
```

Retrieves the index of the character following the last character in the requested field.

Returns:

the end index

setBeginIndex

```
public void setBeginIndex(int bi)
```

Sets the begin index. For use by subclasses of Format.

Parameters:

bi - the begin index

Since:

1.2

setEndIndex

```
public void setEndIndex(int ei)
```

Sets the end index. For use by subclasses of Format.

Parameters:

ei - the end index

Since:

1.2

equals

```
public boolean equals(Object obj)
```

Overrides equals

Overrides:

equals in class Object

Parameters:

obj - the reference object with which to compare.

Returns:

`true if this object is the same as the obj argument; false otherwise.`

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

Returns a hash code for this FieldPosition.

Overrides:

`hashCode` in class `Object`

Returns:

`a hash code value for this object`

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

toString

```
public String toString()
```

Return a string representation of this FieldPosition.

Overrides:

`toString` in class `Object`

Returns:

`a string representation of this object`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.