JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text

Class Format.Field

java.lang.Object
    java.text.AttributedCharacterIterator.Attribute
        java.text.Format.Field

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

DateFormat.Field, MessageFormat.Field, NumberFormat.Field

Enclosing class:

Format

```
public static class Format.Field
extends AttributedCharacterIterator.Attribute
```

Defines constants that are used as attribute keys in the `AttributedCharacterIterator` returned from `Format.formatToCharacterIterator` and as field identifiers in `FieldPosition`.

Since:

1.4

See Also:

Field Summary

Fields inherited from class java.text.AttributedCharacterIterator.Attribute

INPUT_METHOD_SEGMENT, LANGUAGE, READING

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**Field**(**String** name)	Creates a Field with the specified name.

Method Summary

Methods inherited from class java.text.AttributedCharacterIterator.Attribute

equals, getName, hashCode, readResolve, toString

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Constructor Detail

Field

```
protected Field(String name)
```

Creates a Field with the specified name.

Parameters:

`name` - Name of the attribute

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.