JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text

Class MessageFormat.Field

java.lang.Object
  java.text.AttributedCharacterIterator.Attribute
    java.text.Format.Field
      java.text.MessageFormat.Field

All Implemented Interfaces:

Serializable

Enclosing class:

MessageFormat

```
public static class MessageFormat.Field
extends Format.Field
```

Defines constants that are used as attribute keys in the `AttributedCharacterIterator` returned from `MessageFormat.formatToCharacterIterator`.

Since:

1.4

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
static MessageFormat.Field	ARGUMENT	Constant identifying a portion of a message that was

		generated from an argument passed into `formatToCharacterIterator`.

Fields inherited from class java.text.AttributedCharacterIterator.Attribute

`INPUT_METHOD_SEGMENT`, `LANGUAGE`, `READING`

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**`Field`**(**`String`** name)	Creates a Field with the specified name.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
protected **`Object`**	**`readResolve`**()	Resolves instances being deserialized to the predefined constants.

Methods inherited from class java.text.AttributedCharacterIterator.Attribute

`equals`, `getName`, `hashCode`, `toString`

Methods inherited from class java.lang.Object

`clone`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Field Detail

ARGUMENT

```
public static final MessageFormat.Field ARGUMENT
```

Constant identifying a portion of a message that was generated from an argument passed into `formatToCharacterIterator`. The value associated with the key will be an `Integer` indicating the index in the `arguments` array of the argument from which the text was generated.

Constructor Detail

Field

```
protected Field(String name)
```

Creates a Field with the specified name.

Parameters:

`name - Name of the attribute`

Method Detail

readResolve

```
protected Object readResolve()
                     throws InvalidObjectException
```

Resolves instances being deserialized to the predefined constants.

Overrides:

`readResolve in class AttributedCharacterIterator.Attribute`

Returns:

`resolved MessageFormat.Field constant`

Throws:

```
InvalidObjectException - if the constant could not be resolved.
```

C

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.