JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text

Class NumberFormat.Field

java.lang.Object
  java.text.AttributedCharacterIterator.Attribute
    java.text.Format.Field
      java.text.NumberFormat.Field

All Implemented Interfaces:

Serializable

Enclosing class:

NumberFormat

```
public static class NumberFormat.Field
extends Format.Field
```

Defines constants that are used as attribute keys in the `AttributedCharacterIterator` returned from `NumberFormat.formatToCharacterIterator` and as field identifiers in `FieldPosition`.

Since:

1.4

See Also:

Serialized Form

Field Summary

Fields

Modifier and Type	Field	Description
static NumberFormat.Field	CURRENCY	

		Constant identifying the currency field.
static NumberFormat.Field	DECIMAL_SEPARATOR	Constant identifying the decimal separator field.
static NumberFormat.Field	EXPONENT	Constant identifying the exponent field.
static NumberFormat.Field	EXPONENT_SIGN	Constant identifying the exponent sign field.
static NumberFormat.Field	EXPONENT_SYMBOL	Constant identifying the exponent symbol field.
static NumberFormat.Field	FRACTION	Constant identifying the fraction field.
static NumberFormat.Field	GROUPING_SEPARATOR	Constant identifying the grouping separator field.
static NumberFormat.Field	INTEGER	Constant identifying the integer field.
static NumberFormat.Field	PERCENT	Constant identifying the percent field.
static NumberFormat.Field	PERMILLE	Constant identifying the permille field.
static NumberFormat.Field	SIGN	Constant identifying the sign field.

Fields inherited from class java.text.AttributedCharacterIterator.Attribute

INPUT_METHOD_SEGMENT, LANGUAGE, READING

Constructor Summary

Constructors

Modifier	Constructor	Description

protected	**Field**(**String** name)	Creates a Field instance with the specified name.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
protected **Object**	**readResolve**()	Resolves instances being deserialized to the predefined constants.

Methods inherited from class java.text.AttributedCharacterIterator.Attribute

equals, getName, hashCode, toString

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

INTEGER

```
public static final NumberFormat.Field INTEGER
```

Constant identifying the integer field.

FRACTION

```
public static final NumberFormat.Field FRACTION
```

Constant identifying the fraction field.

EXPONENT

```
public static final NumberFormat.Field EXPONENT
```

Constant identifying the exponent field.

DECIMAL_SEPARATOR

```
public static final NumberFormat.Field DECIMAL_SEPARATOR
```

Constant identifying the decimal separator field.

SIGN

```
public static final NumberFormat.Field SIGN
```

Constant identifying the sign field.

GROUPING_SEPARATOR

```
public static final NumberFormat.Field GROUPING_SEPARATOR
```

Constant identifying the grouping separator field.

EXPONENT_SYMBOL

```
public static final NumberFormat.Field EXPONENT_SYMBOL
```

Constant identifying the exponent symbol field.

PERCENT

```
public static final NumberFormat.Field PERCENT
```

Constant identifying the percent field.

PERMILLE

```
public static final NumberFormat.Field PERMILLE
```

Constant identifying the permille field.

CURRENCY

```
public static final NumberFormat.Field CURRENCY
```

Constant identifying the currency field.

EXPONENT_SIGN

```
public static final NumberFormat.Field EXPONENT_SIGN
```

Constant identifying the exponent sign field.

Constructor Detail

Field

```
protected Field(String name)
```

Creates a Field instance with the specified name.

Parameters:

`name - Name of the attribute`

Method Detail

readResolve

```
protected Object readResolve()
                     throws InvalidObjectException
```

Resolves instances being deserialized to the predefined constants.

Overrides:

`readResolve in class AttributedCharacterIterator.Attribute`

Returns:

`resolved NumberFormat.Field constant`

Throws:

`InvalidObjectException` - if the constant could not be resolved.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.