JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text.spi

Class BreakIteratorProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.text.spi.BreakIteratorProvider

```
public abstract class BreakIteratorProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide concrete implementations of the `BreakIterator` class.

Since:

1.6

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**BreakIteratorProvider**()	Sole constructor.

Method Summary

Abstract Methods

Modifier and Type	Method	Description
abstract **BreakIterator**	**getCharacterInstance**(**Locale** locale)	Returns a new BreakIterator instance for

		character breaks for the given locale.
abstract **BreakIterator**	**getLineInstance**(**Locale** locale)	Returns a new BreakIterator instance for **line breaks** for the given locale.
abstract **BreakIterator**	**getSentenceInstance**(**Locale** locale)	Returns a new BreakIterator instance for **sentence breaks** for the given locale.
abstract **BreakIterator**	**getWordInstance**(**Locale** locale)	Returns a new BreakIterator instance for **word breaks** for the given locale.

Methods inherited from class java.util.spi.LocaleServiceProvider

getAvailableLocales, isSupportedLocale

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

BreakIteratorProvider

```
protected BreakIteratorProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Detail

getWordInstance

```
public abstract BreakIterator getWordInstance(Locale locale)
```

Returns a new `BreakIterator` instance for word breaks for the given locale.

Parameters:

`locale - the desired locale`

Returns:

`A break iterator for word breaks`

Throws:

`NullPointerException - if locale is null`

`IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().`

See Also:

`BreakIterator.getWordInstance(java.util.Locale)`

getLineInstance

```
public abstract BreakIterator getLineInstance(Locale locale)
```

Returns a new `BreakIterator` instance for line breaks for the given locale.

Parameters:

`locale - the desired locale`

Returns:

`A break iterator for line breaks`

Throws:

`NullPointerException - if locale is null`

`IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().`

See Also:

`BreakIterator.getLineInstance(java.util.Locale)`

getCharacterInstance

```
public abstract BreakIterator getCharacterInstance(Locale locale)
```

Returns a new `BreakIterator` instance for character breaks for the given locale.

Parameters:

`locale - the desired locale`

Returns:

`A break iterator for character breaks`

Throws:

`NullPointerException - if locale is null`

`IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().`

See Also:

`BreakIterator.getCharacterInstance(java.util.Locale)`

getSentenceInstance

`public abstract BreakIterator getSentenceInstance(Locale locale)`

Returns a new `BreakIterator` instance for sentence breaks for the given locale.

Parameters:

`locale - the desired locale`

Returns:

`A break iterator for sentence breaks`

Throws:

`NullPointerException - if locale is null`

`IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().`

See Also:

`BreakIterator.getSentenceInstance(java.util.Locale)`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.