JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text.spi

Class DecimalFormatSymbolsProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.text.spi.DecimalFormatSymbolsProvider

```
public abstract class DecimalFormatSymbolsProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide instances of the `DecimalFormatSymbols` class.

The requested `Locale` may contain an extension for specifying the desired numbering system. For example, `"ar-u-nu-arab"` (in the BCP 47 language tag form) specifies Arabic with the Arabic-Indic digits and symbols, while `"ar-u-nu-latn"` specifies Arabic with the Latin digits and symbols. Refer to the *Unicode Locale Data Markup Language (LDML)* specification for numbering systems.

Since:

`1.6`

See Also:

`Locale.forLanguageTag(String)`, `Locale.getExtension(char)`

Constructor Summary

Constructors

Modifier	Constructor	Description
`protected`	**`DecimalFormatSymbolsProvider()`**	Sole constructor.

Method Summary

Abstract Methods

Modifier and Type	Method	Description
abstract DecimalFormatSymbols	getInstance(Locale locale)	Returns a new DecimalFormatSymbols instance for the specified locale.

Methods inherited from class java.util.spi.LocaleServiceProvider

getAvailableLocales, isSupportedLocale

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

DecimalFormatSymbolsProvider

```
protected DecimalFormatSymbolsProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Detail

getInstance

```
public abstract DecimalFormatSymbols getInstance(Locale locale)
```

Returns a new DecimalFormatSymbols instance for the specified locale.

Parameters:

locale - the desired locale

Returns:

a DecimalFormatSymbols instance.

Throws:

`NullPointerException` - if locale is null

`IllegalArgumentException` - if locale isn't one of the locales returned from `getAvailableLocales()`.

See Also:

`DecimalFormatSymbols.getInstance(java.util.Locale)`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.