JavaScript is disabled on your browser.

compact1, compact2, compact3

java.text.spi

Class NumberFormatProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.text.spi.NumberFormatProvider

```
public abstract class NumberFormatProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide concrete implementations of the `NumberFormat` class.

Since:

1.6

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	`NumberFormatProvider()`	Sole constructor.

Method Summary

Abstract Methods

Modifier and Type	Method	Description
abstract `NumberFormat`	`getCurrencyInstance(Locale locale)`	Returns a new `NumberFormat`

		instance which formats monetary values for the specified locale.
abstract **NumberFormat**	**getIntegerInstance**(**Locale** locale)	Returns a new `NumberFormat` instance which formats integer values for the specified locale.
abstract **NumberFormat**	**getNumberInstance**(**Locale** locale)	Returns a new general-purpose `NumberFormat` instance for the specified locale.
abstract **NumberFormat**	**getPercentInstance**(**Locale** locale)	Returns a new `NumberFormat` instance which formats percentage values for the specified locale.

Methods inherited from class java.util.spi.LocaleServiceProvider

`getAvailableLocales`, `isSupportedLocale`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

NumberFormatProvider

```
protected NumberFormatProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Detail

getCurrencyInstance

```
public abstract NumberFormat getCurrencyInstance(Locale locale)
```

Returns a new `NumberFormat` instance which formats monetary values for the specified locale.

Parameters:

`locale - the desired locale.`

Returns:

`a currency formatter`

Throws:

`NullPointerException - if locale is null`

`IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().`

See Also:

`NumberFormat.getCurrencyInstance(java.util.Locale)`

getIntegerInstance

```
public abstract NumberFormat getIntegerInstance(Locale locale)
```

Returns a new `NumberFormat` instance which formats integer values for the specified locale. The returned number format is configured to round floating point numbers to the nearest integer using half-even rounding (see `HALF_EVEN`) for formatting, and to parse only the integer part of an input string (see `isParseIntegerOnly`).

Parameters:

`locale - the desired locale`

Returns:

`a number format for integer values`

Throws:

NullPointerException - if locale is null

IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().

See Also:

NumberFormat.getIntegerInstance(java.util.Locale)

getNumberInstance

public abstract NumberFormat getNumberInstance(Locale locale)

Returns a new general-purpose NumberFormat instance for the specified locale.

Parameters:

locale - the desired locale

Returns:

a general-purpose number formatter

Throws:

NullPointerException - if locale is null

IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().

See Also:

NumberFormat.getNumberInstance(java.util.Locale)

getPercentInstance

public abstract NumberFormat getPercentInstance(Locale locale)

Returns a new NumberFormat instance which formats percentage values for the specified locale.

Parameters:

locale - the desired locale

Returns:

a percent formatter

Throws:

NullPointerException - if locale is null

IllegalArgumentException - if locale isn't one of the locales returned from getAvailableLocales().

See Also:

```
NumberFormat.getPercentInstance(java.util.Locale)
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.