JavaScript is disabled on your browser.

compact1, compact2, compact3

java.time.chrono

Class HijrahDate

java.lang.Object
    java.time.chrono.HijrahDate

All Implemented Interfaces:

`Serializable`, `Comparable<ChronoLocalDate>`, `ChronoLocalDate`, `Temporal`, `TemporalAccessor`, `TemporalAdjuster`

```
public final class HijrahDate
extends Object
implements ChronoLocalDate, Serializable
```

A date in the Hijrah calendar system.

This date operates using one of several variants of the Hijrah calendar.

The Hijrah calendar has a different total of days in a year than Gregorian calendar, and the length of each month is based on the period of a complete revolution of the moon around the earth (as between successive new moons). Refer to the `HijrahChronology` for details of supported variants.

Each HijrahDate is created bound to a particular HijrahChronology, The same chronology is propagated to each HijrahDate computed from the date. To use a different Hijrah variant, its HijrahChronology can be used to create new HijrahDate instances. Alternatively, the `withVariant(java.time.chrono.HijrahChronology)` method can be used to convert to a new HijrahChronology.

This is a value-based class; use of identity-sensitive operations (including reference equality (==), identity hash code, or synchronization) on instances of `HijrahDate` may have unpredictable results and should be avoided. The `equals` method should be used for comparisons.

Implementation Requirements:

This class is immutable and thread-safe.

Since:

1.8

See Also:

Serialized Form

Method Summary

Concrete Methods

Modifier and Type	Method	Descrip
ChronoLocalDateTime<HijrahDate>	atTime(LocalTime localTime)	Combin with a time t Chronol
boolean	equals(Object obj)	Compar another includin chronol
static HijrahDate	from(TemporalAccessor temporal)	Obtains of the I Qura ca tempor
HijrahChronology	getChronology()	Gets th this dat Hijrah system.
HijrahEra	getEra()	Gets th applica
long	getLong(TemporalField field)	Gets th specifie long.
int	hashCode()	A hash date.
boolean	isLeapYear()	Checks leap ye the Hijr system
int	lengthOfMonth()	

		Returns the mon by this
int	**lengthOfYear**()	Returns the yea by this
HijrahDate	**minus**(long amountToSubtract, **TemporalUnit** unit)	Returns the sam object v specifie subtrac
HijrahDate	**minus**(**TemporalAmount** amount)	Returns the sam object v subtrac
static **HijrahDate**	**now**()	Obtains Hijrah Islamic calenda time-zo
static **HijrahDate**	**now**(**Clock** clock)	Obtains Hijrah Islamic calenda specifie
static **HijrahDate**	**now**(**ZoneId** zone)	Obtains Hijrah Islamic calenda specifie
static **HijrahDate**	**of**(int prolepticYear, int month, int dayOfMonth)	Obtains of the I Qura ca the pro month- of-mont
HijrahDate	**plus**(long amountToAdd, **TemporalUnit** unit)	Returns the sam object v specifie added.

HijrahDate	plus(TemporalAmount amount)	Returns the sam object v added.
ValueRange	range(TemporalField field)	Gets th values f specifie
long	toEpochDay()	Conver the Epo
String	toString()	Returns represe object.
ChronoPeriod	until(ChronoLocalDate endDate)	Calcula betwee another Chrono
long	until(Temporal endExclusive, TemporalUnit unit)	Calcula of time date in specifie
HijrahDate	with(TemporalAdjuster adjuster)	Returns object c type as with th made.
HijrahDate	with(TemporalField field, long newValue)	Returns the sam object v specifie
HijrahDate	withVariant(HijrahChronology chronology)	Returns with th request

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Methods inherited from interface java.time.chrono.ChronoLocalDate

adjustInto, compareTo, format, isAfter, isBefore, isEqual, isSupported, isSupported, query, timeLineOrder, toString, until

Methods inherited from interface java.time.temporal.TemporalAccessor

get

Method Detail

now

```
public static HijrahDate now()
```

Obtains the current `HijrahDate` of the Islamic Umm Al-Qura calendar in the default time-zone.

This will query the `system clock` in the default time-zone to obtain the current date.

Using this method will prevent the ability to use an alternate clock for testing because the clock is hard-coded.

Returns:

`the current date using the system clock and default time-zone, not null`

now

```
public static HijrahDate now(ZoneId zone)
```

Obtains the current `HijrahDate` of the Islamic Umm Al-Qura calendar in the specified time-zone.

This will query the `system clock` to obtain the current date. Specifying the time-zone avoids dependence on the default time-zone.

Using this method will prevent the ability to use an alternate clock for testing because the clock is hard-coded.

Parameters:

`zone - the zone ID to use, not null`

Returns:

the current date using the system clock, not null

now

```
public static HijrahDate now(Clock clock)
```

Obtains the current `HijrahDate` of the Islamic Umm Al-Qura calendar from the specified clock.

This will query the specified clock to obtain the current date - today. Using this method allows the use of an alternate clock for testing. The alternate clock may be introduced using dependency injection.

Parameters:

`clock` - the clock to use, not null

Returns:

the current date, not null

Throws:

`DateTimeException` - if the current date cannot be obtained

of

```
public static HijrahDate of(int prolepticYear,
                            int month,
                            int dayOfMonth)
```

Obtains a `HijrahDate` of the Islamic Umm Al-Qura calendar from the proleptic-year, month-of-year and day-of-month fields.

This returns a `HijrahDate` with the specified fields. The day must be valid for the year and month, otherwise an exception will be thrown.

Parameters:

`prolepticYear` - the Hijrah proleptic-year

`month` - the Hijrah month-of-year, from 1 to 12

`dayOfMonth` - the Hijrah day-of-month, from 1 to 30

Returns:

the date in Hijrah calendar system, not null

Throws:

`DateTimeException` - if the value of any field is out of range, or if the day-of-month is invalid for the month-year

from

`public static HijrahDate from(TemporalAccessor temporal)`

Obtains a `HijrahDate` of the Islamic Umm Al-Qura calendar from a temporal object.

This obtains a date in the Hijrah calendar system based on the specified temporal. A `TemporalAccessor` represents an arbitrary set of date and time information, which this factory converts to an instance of `HijrahDate`.

The conversion typically uses the `EPOCH_DAY` field, which is standardized across calendar systems.

This method matches the signature of the functional interface `TemporalQuery` allowing it to be used as a query via method reference, `HijrahDate::from`.

Specified by:

`from` in interface `ChronoLocalDate`

Parameters:

`temporal - the temporal object to convert, not null`

Returns:

`the date in Hijrah calendar system, not null`

Throws:

`DateTimeException - if unable to convert to a HijrahDate`

See Also:

`Chronology.date(TemporalAccessor)`

getChronology

`public HijrahChronology getChronology()`

Gets the chronology of this date, which is the Hijrah calendar system.

The `Chronology` represents the calendar system in use. The era and other fields in `ChronoField` are defined by the chronology.

Specified by:

`getChronology` in interface `ChronoLocalDate`

Returns:

`the Hijrah chronology, not null`

getEra

```
public HijrahEra getEra()
```

Gets the era applicable at this date.

The Hijrah calendar system has one era, 'AH', defined by `HijrahEra`.

Specified by:

`getEra` in interface `ChronoLocalDate`

Returns:

the era applicable at this date, not null

lengthOfMonth

```
public int lengthOfMonth()
```

Returns the length of the month represented by this date.

This returns the length of the month in days. Month lengths in the Hijrah calendar system vary between 29 and 30 days.

Specified by:

`lengthOfMonth` in interface `ChronoLocalDate`

Returns:

the length of the month in days

lengthOfYear

```
public int lengthOfYear()
```

Returns the length of the year represented by this date.

This returns the length of the year in days. A Hijrah calendar system year is typically shorter than that of the ISO calendar system.

Specified by:

`lengthOfYear` in interface `ChronoLocalDate`

Returns:

the length of the year in days

range

```
public ValueRange range(TemporalField field)
```

Description copied from interface: TemporalAccessor
Gets the range of valid values for the specified field.

All fields can be expressed as a `long` integer. This method returns an object that describes the valid range for that value. The value of this temporal object is used to enhance the accuracy of the returned range. If the date-time cannot return the range, because the field is unsupported or for some other reason, an exception will be thrown.

Note that the result only describes the minimum and maximum valid values and it is important not to read too much into them. For example, there could be values within the range that are invalid for the field.

Specified by:

`range` in interface `TemporalAccessor`

Parameters:

`field - the field to query the range for, not null`

Returns:

`the range of valid values for the field, not null`

getLong

```
public long getLong(TemporalField field)
```

Description copied from interface: TemporalAccessor
Gets the value of the specified field as a `long`.

This queries the date-time for the value of the specified field. The returned value may be outside the valid range of values for the field. If the date-time cannot return the value, because the field is unsupported or for some other reason, an exception will be thrown.

Specified by:

`getLong` in interface `TemporalAccessor`

Parameters:

`field - the field to get, not null`

Returns:

`the value for the field`

with

```
public HijrahDate with(TemporalField field,
                       long newValue)
```

Description copied from interface: `ChronoLocalDate`

Returns an object of the same type as this object with the specified field altered.

This returns a new object based on this one with the value for the specified field changed. For example, on a `LocalDate`, this could be used to set the year, month or day-of-month. The returned object will have the same observable type as this object.

In some cases, changing a field is not fully defined. For example, if the target object is a date representing the 31st January, then changing the month to February would be unclear. In cases like this, the field is responsible for resolving the result. Typically it will choose the previous valid date, which would be the last valid day of February in this example.

Specified by:

`with` in interface `ChronoLocalDate`

Specified by:

`with` in interface `Temporal`

Parameters:

`field` - the field to set in the result, not null

`newValue` - the new value of the field in the result

Returns:

an object of the same type with the specified field set, not null

with

```
public HijrahDate with(TemporalAdjuster adjuster)
```

Returns an adjusted object of the same type as this object with the adjustment made.

This adjusts this date-time according to the rules of the specified adjuster. A simple adjuster might simply set the one of the fields, such as the year field. A more complex adjuster might set the date to the last day of the month. A selection of common adjustments is provided in `TemporalAdjusters`. These include finding the "last day of the month" and "next Wednesday". The adjuster is responsible for handling special cases, such as the varying lengths of month and leap years.

Some example code indicating how and why this method is used:

```
  date = date.with(Month.JULY);        // most key classes implement TemporalAdju
  date = date.with(lastDayOfMonth());  // static import from Adjusters
  date = date.with(next(WEDNESDAY));   // static import from Adjusters and DayOfW
```

Specified by:

`with` in interface `ChronoLocalDate`

Specified by:

`with` in interface `Temporal`

Parameters:

`adjuster` - the adjuster to use, not null

Returns:

an object of the same type with the specified adjustment made, not null

Throws:

`DateTimeException` - if unable to make the adjustment. For example, if the adjuster requires an ISO chronology

`ArithmeticException` - if numeric overflow occurs

withVariant

`public HijrahDate withVariant(HijrahChronology chronology)`

Returns a `HijrahDate` with the Chronology requested.

The year, month, and day are checked against the new requested HijrahChronology. If the chronology has a shorter month length for the month, the day is reduced to be the last day of the month.

Parameters:

`chronology` - the new HijrahChonology, non-null

Returns:

a HijrahDate with the requested HijrahChronology, non-null

plus

`public HijrahDate plus(TemporalAmount amount)`

Returns an object of the same type as this object with an amount added.

This adjusts this temporal, adding according to the rules of the specified amount. The amount is typically a `Period` but may be any other type implementing the `TemporalAmount` interface, such as `Duration`.

Some example code indicating how and why this method is used:

```
  date = date.plus(period);                // add a Period instance
  date = date.plus(duration);              // add a Duration instance
  date = date.plus(workingDays(6));        // example user-written workingDays me
```

Note that calling `plus` followed by `minus` is not guaranteed to return the same date-time.

Specified by:

`plus` in interface `ChronoLocalDate`

Specified by:

`plus` in interface `Temporal`

Parameters:

`amount` - the amount to add, not null

Returns:

an object of the same type with the specified adjustment made, not null

Throws:

`DateTimeException` - if the addition cannot be made

`ArithmeticException` - if numeric overflow occurs

minus

```
public HijrahDate minus(TemporalAmount amount)
```

Returns an object of the same type as this object with an amount subtracted.

This adjusts this temporal, subtracting according to the rules of the specified amount. The amount is typically a `Period` but may be any other type implementing the `TemporalAmount` interface, such as `Duration`.

Some example code indicating how and why this method is used:

```
  date = date.minus(period);               // subtract a Period instance
  date = date.minus(duration);             // subtract a Duration instance
  date = date.minus(workingDays(6));       // example user-written workingDays me
```

Note that calling `plus` followed by `minus` is not guaranteed to return the same date-time.

Specified by:

`minus` in interface `ChronoLocalDate`

Specified by:

minus in interface Temporal

Parameters:

amount - the amount to subtract, not null

Returns:

an object of the same type with the specified adjustment made, not null

Throws:

DateTimeException - if the subtraction cannot be made

ArithmeticException - if numeric overflow occurs

toEpochDay

public long toEpochDay()

Description copied from interface: ChronoLocalDate

Converts this date to the Epoch Day.

The Epoch Day count is a simple incrementing count of days where day 0 is 1970-01-01 (ISO). This definition is the same for all chronologies, enabling conversion.

This default implementation queries the EPOCH_DAY field.

Specified by:

toEpochDay in interface ChronoLocalDate

Returns:

the Epoch Day equivalent to this date

isLeapYear

public boolean isLeapYear()

Checks if the year is a leap year, according to the Hijrah calendar system rules.

Specified by:

isLeapYear in interface ChronoLocalDate

Returns:

true if this date is in a leap year

plus

```
public HijrahDate plus(long amountToAdd,
                       TemporalUnit unit)
```

Description copied from interface: ChronoLocalDate

Returns an object of the same type as this object with the specified period added.

This method returns a new object based on this one with the specified period added. For example, on a `LocalDate`, this could be used to add a number of years, months or days. The returned object will have the same observable type as this object.

In some cases, changing a field is not fully defined. For example, if the target object is a date representing the 31st January, then adding one month would be unclear. In cases like this, the field is responsible for resolving the result. Typically it will choose the previous valid date, which would be the last valid day of February in this example.

Specified by:

`plus` in interface `ChronoLocalDate`

Specified by:

`plus` in interface `Temporal`

Parameters:

`amountToAdd - the amount of the specified unit to add, may be negative`

`unit - the unit of the amount to add, not null`

Returns:

`an object of the same type with the specified period added, not null`

minus

```
public HijrahDate minus(long amountToSubtract,
                        TemporalUnit unit)
```

Description copied from interface: ChronoLocalDate

Returns an object of the same type as this object with the specified period subtracted.

This method returns a new object based on this one with the specified period subtracted. For example, on a `LocalDate`, this could be used to subtract a number of years, months or days. The returned object will have the same observable type as this object.

In some cases, changing a field is not fully defined. For example, if the target object is a date representing the 31st March, then subtracting one month would be unclear. In cases like this, the field is responsible for resolving the result. Typically it will choose the previous valid date, which would be the last valid day of February in this example.

Specified by:

`minus` in interface `ChronoLocalDate`

Specified by:

`minus` in interface `Temporal`

Parameters:

`amountToSubtract` - the amount of the specified unit to subtract, may be negative

`unit` - the unit of the amount to subtract, not null

Returns:

an object of the same type with the specified period subtracted, not null

atTime

```
public final ChronoLocalDateTime<HijrahDate> atTime(LocalTime localTime)
```

Description copied from interface: `ChronoLocalDate`

Combines this date with a time to create a `ChronoLocalDateTime`.

This returns a `ChronoLocalDateTime` formed from this date at the specified time. All possible combinations of date and time are valid.

Specified by:

`atTime` in interface `ChronoLocalDate`

Parameters:

`localTime` - the local time to use, not null

Returns:

the local date-time formed from this date and the specified time, not null

until

```
public ChronoPeriod until(ChronoLocalDate endDate)
```

Description copied from interface: `ChronoLocalDate`

Calculates the period between this date and another date as a `ChronoPeriod`.

This calculates the period between two dates. All supplied chronologies calculate the period using years, months and days, however the `ChronoPeriod` API allows the period to be represented using other units.

The start and end points are `this` and the specified date. The result will be negative if the end is before the start. The negative sign will be the same in each of year, month and day.

The calculation is performed using the chronology of this date. If necessary, the input date will be converted to match.

This instance is immutable and unaffected by this method call.

Specified by:

`until` in interface `ChronoLocalDate`

Parameters:

`endDate - the end date, exclusive, which may be in any chronology, not null`

Returns:

`the period between this date and the end date, not null`

equals

```
public boolean equals(Object obj)
```

Compares this date to another date, including the chronology.

Compares this `HijrahDate` with another ensuring that the date is the same.

Only objects of type `HijrahDate` are compared, other types return false. To compare the dates of two `TemporalAccessor` instances, including dates in two different chronologies, use `ChronoField.EPOCH_DAY` as a comparator.

Specified by:

`equals` in interface `ChronoLocalDate`

Parameters:

`obj - the object to check, null returns false`

Returns:

`true if this is equal to the other date and the Chronologies are equal`

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

A hash code for this date.

Specified by:

`hashCode` in interface `ChronoLocalDate`

Returns:

a suitable hash code based only on the Chronology and the date

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

until

```
public long until(Temporal endExclusive,
                  TemporalUnit unit)
```

Description copied from interface: `ChronoLocalDate`

Calculates the amount of time until another date in terms of the specified unit.

This calculates the amount of time between two `ChronoLocalDate` objects in terms of a single `TemporalUnit`. The start and end points are `this` and the specified date. The result will be negative if the end is before the start. The `Temporal` passed to this method is converted to a `ChronoLocalDate` using `Chronology.date(TemporalAccessor)`. The calculation returns a whole number, representing the number of complete units between the two dates. For example, the amount in days between two dates can be calculated using `startDate.until(endDate, DAYS)`.

There are two equivalent ways of using this method. The first is to invoke this method. The second is to use `TemporalUnit.between(Temporal, Temporal)`:

```
// these two lines are equivalent
amount = start.until(end, MONTHS);
amount = MONTHS.between(start, end);
```

The choice should be made based on which makes the code more readable.

The calculation is implemented in this method for `ChronoUnit`. The units `DAYS`, `WEEKS`, `MONTHS`, `YEARS`, `DECADES`, `CENTURIES`, `MILLENNIA` and `ERAS` should be supported by all implementations. Other `ChronoUnit` values will throw an exception.

If the unit is not a `ChronoUnit`, then the result of this method is obtained by invoking `TemporalUnit.between(Temporal, Temporal)` passing `this` as the first argument and the converted input temporal as the second argument.

This instance is immutable and unaffected by this method call.

Specified by:

`until` in interface `ChronoLocalDate`

Specified by:

`until` in interface `Temporal`

Parameters:

`endExclusive - the end date, exclusive, which is converted to a ChronoLocalDate in the same chronology, not null`

`unit - the unit to measure the amount in, not null`

Returns:

`the amount of time between this date and the end date`

toString

`public String toString()`

Description copied from class: `Object`

Returns a string representation of the object. In general, the `toString` method returns a string that "textually represents" this object. The result should be a concise but informative representation that is easy for a person to read. It is recommended that all subclasses override this method.

The `toString` method for class `Object` returns a string consisting of the name of the class of which the object is an instance, the at-sign character `@', and the unsigned hexadecimal representation of the hash code of the object. In other words, this method returns a string equal to the value of:

```
getClass().getName() + '@' + Integer.toHexString(hashCode())
```

Specified by:

`toString` in interface `ChronoLocalDate`

Overrides:

`toString` in class `Object`

Returns:

a string representation of the object.

C

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.