JavaScript is disabled on your browser.

compact1, compact2, compact3

java.time.chrono

Enum HijrahEra

java.lang.Object
    java.lang.Enum<HijrahEra>
        java.time.chrono.HijrahEra

All Implemented Interfaces:

Serializable, Comparable<HijrahEra>, Era, TemporalAccessor, TemporalAdjuster

---

```
public enum HijrahEra
extends Enum<HijrahEra>
implements Era
```

An era in the Hijrah calendar system.

The Hijrah calendar system has only one era covering the proleptic years greater than zero.

Do not use `ordinal()` to obtain the numeric representation of `HijrahEra`. Use `getValue()` instead.

Implementation Requirements:

This is an immutable and thread-safe enum.

Since:

1.8

Enum Constant Summary

Enum Constants

Enum Constant	Description

AH	The singleton instance for the current era, 'Anno Hegirae', which has the numeric value 1.

Method Summary

Instance Methods | **Concrete Methods**

Modifier and Type	Method	Description
String	**getDisplayName**(**TextStyle** style, **Locale** locale)	Gets the textual representation of this era.
int	**getValue**()	Gets the numeric era `int` value.
static **HijrahEra**	**of**(int hijrahEra)	Obtains an instance of `HijrahEra` from an `int` value.
ValueRange	**range**(**TemporalField** field)	Gets the range of valid values for the specified field.
static **HijrahEra**	**valueOf**(**String** name)	Returns the enum constant of this type with the specified name.
static **HijrahEra**[]	**values**()	Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

clone, compareTo, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Methods inherited from interface java.time.chrono.Era

adjustInto, get, getLong, isSupported, query

Enum Constant Detail

AH

```
public static final HijrahEra AH
```

The singleton instance for the current era, 'Anno Hegirae', which has the numeric value 1.

Method Detail

values

```
public static HijrahEra[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (HijrahEra c : HijrahEra.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static HijrahEra valueOf(String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

`name - the name of the enum constant to be returned.`

Returns:

`the enum constant with the specified name`

Throws:

`IllegalArgumentException - if this enum type has no constant with the specified name`

`NullPointerException - if the argument is null`

of

```
public static HijrahEra of(int hijrahEra)
```

Obtains an instance of `HijrahEra` from an `int` value.

The current era, which is the only accepted value, has the value 1

Parameters:

`hijrahEra - the era to represent, only 1 supported`

Returns:

`the HijrahEra.AH singleton, not null`

Throws:

`DateTimeException - if the value is invalid`

getValue

```
public int getValue()
```

Gets the numeric era `int` value.

The era AH has the value 1.

Specified by:

`getValue` in interface `Era`

Returns:

the era value, 1 (AH)

range

```
public ValueRange range(TemporalField field)
```

Gets the range of valid values for the specified field.

The range object expresses the minimum and maximum valid values for a field. This era is used to enhance the accuracy of the returned range. If it is not possible to return the range, because the field is not supported or for some other reason, an exception is thrown.

If the field is a `ChronoField` then the query is implemented here. The `ERA` field returns the range. All other `ChronoField` instances will throw an `UnsupportedTemporalTypeException`.

If the field is not a `ChronoField`, then the result of this method is obtained by invoking `TemporalField.rangeRefinedBy(TemporalAccessor)` passing `this` as the argument. Whether the range can be obtained is determined by the field.

The `ERA` field returns a range for the one valid Hijrah era.

Specified by:

`range` in interface `Era`

Specified by:

`range` in interface `TemporalAccessor`

Parameters:

field - the field to query the range for, not null

Returns:

the range of valid values for the field, not null

Throws:

`DateTimeException` - if the range for the field cannot be obtained

UnsupportedTemporalTypeException - if the unit is not supported

getDisplayName

```
public String getDisplayName(TextStyle style,
                             Locale locale)
```

Gets the textual representation of this era.

This returns the textual name used to identify the era, suitable for presentation to the user. The parameters control the style of the returned text and the locale.

If no textual mapping is found then the numeric value is returned.

Specified by:

getDisplayName in interface Era

Parameters:

style - the style of the text required, not null

locale - the locale to use, not null

Returns:

the text value of the era, not null

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.