JavaScript is disabled on your browser.

compact1, compact2, compact3

java.time.chrono

Enum IsoEra

java.lang.Object
    java.lang.Enum<IsoEra>
        java.time.chrono.IsoEra

All Implemented Interfaces:

Serializable, Comparable<IsoEra>, Era, TemporalAccessor, TemporalAdjuster

---

```
public enum IsoEra
extends Enum<IsoEra>
implements Era
```

An era in the ISO calendar system.

The ISO-8601 standard does not define eras. A definition has therefore been created with two eras - 'Current era' (CE) for years on or after 0001-01-01 (ISO), and 'Before current era' (BCE) for years before that.

year-of-era	era	proleptic-year
2	CE	2
1	CE	1
1	BCE	0
2	BCE	-1

Do not use `ordinal()` to obtain the numeric representation of `IsoEra`. Use `getValue()` instead.

Implementation Requirements:

This is an immutable and thread-safe enum.

Since:

1.8

Enum Constant Summary

Enum Constants

Enum Constant	Description
BCE	The singleton instance for the era before the current one, 'Before Current Era', which has the numeric value 0.
CE	The singleton instance for the current era, 'Current Era', which has the numeric value 1.

Method Summary

Instance Methods

Concrete Methods

Modifier and Type	Method	Description
`int`	**`getValue`**`()`	Gets the numeric era `int` value.
`static` **`IsoEra`**	**`of`**`(int isoEra)`	Obtains an instance of `IsoEra` from an `int` value.
`static` **`IsoEra`**	**`valueOf`**`(`**`String`**` name)`	Returns the enum constant of this type with the specified name.
`static` **`IsoEra`**`[]`	**`values`**`()`	Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

`clone`, `compareTo`, `equals`, `finalize`, `getDeclaringClass`, `hashCode`, `name`, `ordinal`, `toString`, `valueOf`

Methods inherited from class java.lang.Object

`getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Methods inherited from interface java.time.chrono.Era

adjustInto, get, getDisplayName, getLong, isSupported, query, range

Enum Constant Detail

BCE

```
public static final IsoEra BCE
```

The singleton instance for the era before the current one, 'Before Current Era', which has the numeric value 0.

CE

```
public static final IsoEra CE
```

The singleton instance for the current era, 'Current Era', which has the numeric value 1.

Method Detail

values

```
public static IsoEra[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (IsoEra c : IsoEra.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static IsoEra valueOf(String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

`name - the name of the enum constant to be returned.`

Returns:

`the enum constant with the specified name`

Throws:

`IllegalArgumentException - if this enum type has no constant with the specified name`

`NullPointerException - if the argument is null`

of

`public static IsoEra of(int isoEra)`

Obtains an instance of `IsoEra` from an `int` value.

`IsoEra` is an enum representing the ISO eras of BCE/CE. This factory allows the enum to be obtained from the `int` value.

Parameters:

`isoEra - the BCE/CE value to represent, from 0 (BCE) to 1 (CE)`

Returns:

`the era singleton, not null`

Throws:

`DateTimeException - if the value is invalid`

getValue

`public int getValue()`

Gets the numeric era `int` value.

The era BCE has the value 0, while the era CE has the value 1.

Specified by:

`getValue in interface Era`

Returns:

`the era value, from 0 (BCE) to 1 (CE)`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.