JavaScript is disabled on your browser.

compact1, compact2, compact3

java.time.format

Class DecimalStyle

java.lang.Object
    java.time.format.DecimalStyle

```
public final class DecimalStyle
extends Object
```

Localized decimal style used in date and time formatting.

A significant part of dealing with dates and times is the localization. This class acts as a central point for accessing the information.

Implementation Requirements:

This class is immutable and thread-safe.

Since:

1.8

Field Summary

Fields

Modifier and Type	Field	Description
static DecimalStyle	STANDARD	The standard set of non-localized decimal style symbols.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
boolean	**equals**(**Object** obj)	Checks if this DecimalStyle is equal to another DecimalStyle.
static **Set**<**Locale**>	**getAvailableLocales**()	Lists all the locales that are supported.
char	**getDecimalSeparator**()	Gets the character that represents the decimal point.
char	**getNegativeSign**()	Gets the character that represents the negative sign.
char	**getPositiveSign**()	Gets the character that represents the positive sign.
char	**getZeroDigit**()	Gets the character that represents zero.
int	**hashCode**()	A hash code for this DecimalStyle.
static **DecimalStyle**	**of**(**Locale** locale)	Obtains the DecimalStyle for the specified locale.

static **DecimalStyle**	**ofDefaultLocale**()	Obtains the DecimalStyle for the default **FORMAT** locale.
String	**toString**()	Returns a string describing this DecimalStyle.
DecimalStyle	**withDecimalSeparator**(char decimalSeparator)	Returns a copy of the info with a new character that represents the decimal point.
DecimalStyle	**withNegativeSign**(char negativeSign)	Returns a copy of the info with a new character that represents the negative sign.
DecimalStyle	**withPositiveSign**(char positiveSign)	Returns a copy of the info with a new character that represents the positive sign.
DecimalStyle	**withZeroDigit**(char zeroDigit)	Returns a copy of the info with a new character that

		represents zero.

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

STANDARD

```
public static final DecimalStyle STANDARD
```

The standard set of non-localized decimal style symbols.

This uses standard ASCII characters for zero, positive, negative and a dot for the decimal point.

Method Detail

getAvailableLocales

```
public static Set<Locale> getAvailableLocales()
```

Lists all the locales that are supported.

The locale 'en_US' will always be present.

Returns:

a Set of Locales for which localization is supported

ofDefaultLocale

```
public static DecimalStyle ofDefaultLocale()
```

Obtains the DecimalStyle for the default FORMAT locale.

This method provides access to locale sensitive decimal style symbols.

This is equivalent to calling of(Locale.getDefault(Locale.Category.FORMAT)).

Returns:

the decimal style, not null

See Also:

Locale.Category.FORMAT

of

`public static DecimalStyle of(Locale locale)`

Obtains the DecimalStyle for the specified locale.

This method provides access to locale sensitive decimal style symbols.

Parameters:

`locale - the locale, not null`

Returns:

`the decimal style, not null`

getZeroDigit

`public char getZeroDigit()`

Gets the character that represents zero.

The character used to represent digits may vary by culture. This method specifies the zero character to use, which implies the characters for one to nine.

Returns:

`the character for zero`

withZeroDigit

`public DecimalStyle withZeroDigit(char zeroDigit)`

Returns a copy of the info with a new character that represents zero.

The character used to represent digits may vary by culture. This method specifies the zero character to use, which implies the characters for one to nine.

Parameters:

`zeroDigit - the character for zero`

Returns:

`a copy with a new character that represents zero, not null`

getPositiveSign

```
public char getPositiveSign()
```

Gets the character that represents the positive sign.

The character used to represent a positive number may vary by culture. This method specifies the character to use.

Returns:

the character for the positive sign

withPositiveSign

```
public DecimalStyle withPositiveSign(char positiveSign)
```

Returns a copy of the info with a new character that represents the positive sign.

The character used to represent a positive number may vary by culture. This method specifies the character to use.

Parameters:

positiveSign - the character for the positive sign

Returns:

a copy with a new character that represents the positive sign, not null

getNegativeSign

```
public char getNegativeSign()
```

Gets the character that represents the negative sign.

The character used to represent a negative number may vary by culture. This method specifies the character to use.

Returns:

the character for the negative sign

withNegativeSign

```
public DecimalStyle withNegativeSign(char negativeSign)
```

Returns a copy of the info with a new character that represents the negative sign.

The character used to represent a negative number may vary by culture. This method specifies the character to use.

Parameters:

`negativeSign - the character for the negative sign`

Returns:

`a copy with a new character that represents the negative sign, not null`

getDecimalSeparator

```
public char getDecimalSeparator()
```

Gets the character that represents the decimal point.

The character used to represent a decimal point may vary by culture. This method specifies the character to use.

Returns:

`the character for the decimal point`

withDecimalSeparator

```
public DecimalStyle withDecimalSeparator(char decimalSeparator)
```

Returns a copy of the info with a new character that represents the decimal point.

The character used to represent a decimal point may vary by culture. This method specifies the character to use.

Parameters:

`decimalSeparator - the character for the decimal point`

Returns:

`a copy with a new character that represents the decimal point, not null`

equals

```
public boolean equals(Object obj)
```

Checks if this DecimalStyle is equal to another DecimalStyle.

Overrides:

`equals` in class `Object`

Parameters:

obj - the object to check, null returns false

Returns:

true if this is equal to the other date

See Also:

Object.hashCode(), HashMap

hashCode

public int hashCode()

A hash code for this DecimalStyle.

Overrides:

hashCode in class Object

Returns:

a suitable hash code

See Also:

Object.equals(java.lang.Object), System.identityHashCode(java.lang.Object)

toString

public String toString()

Returns a string describing this DecimalStyle.

Overrides:

toString in class Object

Returns:

```
a string description, not null
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.