JavaScript is disabled on your browser.

compact1, compact2, compact3

java.time.format

Enum ResolverStyle

java.lang.Object
    java.lang.Enum<ResolverStyle>
        java.time.format.ResolverStyle

All Implemented Interfaces:

Serializable, Comparable<ResolverStyle>

```
public enum ResolverStyle
extends Enum<ResolverStyle>
```

Enumeration of different ways to resolve dates and times.

Parsing a text string occurs in two phases. Phase 1 is a basic text parse according to the fields added to the builder. Phase 2 resolves the parsed field-value pairs into date and/or time objects. This style is used to control how phase 2, resolving, happens.

Implementation Requirements:

This is an immutable and thread-safe enum.

Since:

1.8

Enum Constant Summary

Enum Constants

Enum Constant	Description
LENIENT	Style to resolve dates and times leniently.
SMART	Style to resolve dates and times in a smart, or intelligent, manner.

STRICT	Style to resolve dates and times strictly.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
static **ResolverStyle**	**valueOf**(**String** name)	Returns the enum constant of this type with the specified name.
static **ResolverStyle**[]	**values**()	Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

clone, compareTo, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Enum Constant Detail

STRICT

```
public static final ResolverStyle STRICT
```

Style to resolve dates and times strictly.

Using strict resolution will ensure that all parsed values are within the outer range of valid values for the field. Individual fields may be further processed for strictness.

For example, resolving year-month and day-of-month in the ISO calendar system using strict mode will ensure that the day-of-month is valid for the year-month, rejecting invalid values.

SMART

```
public static final ResolverStyle SMART
```

Style to resolve dates and times in a smart, or intelligent, manner.

Using smart resolution will perform the sensible default for each field, which may be the same as strict, the same as lenient, or a third behavior. Individual fields will interpret this differently.

For example, resolving year-month and day-of-month in the ISO calendar system using smart mode will ensure that the day-of-month is from 1 to 31, converting any value beyond the last valid day-of-month to be the last valid day-of-month.

LENIENT

```
public static final ResolverStyle LENIENT
```

Style to resolve dates and times leniently.

Using lenient resolution will resolve the values in an appropriate lenient manner. Individual fields will interpret this differently.

For example, lenient mode allows the month in the ISO calendar system to be outside the range 1 to 12. For example, month 15 is treated as being 3 months after month 12.

Method Detail

values

```
public static ResolverStyle[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (ResolverStyle c : ResolverStyle.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static ResolverStyle valueOf(String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

`name - the name of the enum constant to be returned.`

Returns:

`the enum constant with the specified name`

Throws:

`IllegalArgumentException - if this enum type has no constant with the specified name`

`NullPointerException - if the argument is null`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.