JavaScript is disabled on your browser.

compact1, compact2, compact3

java.time.format

Enum TextStyle

java.lang.Object
    java.lang.Enum<TextStyle>
        java.time.format.TextStyle

All Implemented Interfaces:

Serializable, Comparable<TextStyle>

```
public enum TextStyle
extends Enum<TextStyle>
```

Enumeration of the style of text formatting and parsing.

Text styles define three sizes for the formatted text - 'full', 'short' and 'narrow'. Each of these three sizes is available in both 'standard' and 'stand-alone' variations.

The difference between the three sizes is obvious in most languages. For example, in English the 'full' month is 'January', the 'short' month is 'Jan' and the 'narrow' month is 'J'. Note that the narrow size is often not unique. For example, 'January', 'June' and 'July' all have the 'narrow' text 'J'.

The difference between the 'standard' and 'stand-alone' forms is trickier to describe as there is no difference in English. However, in other languages there is a difference in the word used when the text is used alone, as opposed to in a complete date. For example, the word used for a month when used alone in a date picker is different to the word used for month in association with a day and year in a date.

Implementation Requirements:

This is immutable and thread-safe enum.

Enum Constant Summary

Enum Constants	Description
FULL	Full text, typically the full description.
FULL_STANDALONE	Full text for stand-alone use, typically the full description.
NARROW	Narrow text, typically a single letter.
NARROW_STANDALONE	Narrow text for stand-alone use, typically a single letter.
SHORT	Short text, typically an abbreviation.
SHORT_STANDALONE	Short text for stand-alone use, typically an abbreviation.

Method Summary

Instance Methods

Concrete Methods

Modifier and Type	Method	Description
TextStyle	asNormal()	Returns the normal style with the same size.
TextStyle	asStandalone()	Returns the stand-alone style with the same size.
boolean	isStandalone()	Returns true if the Style is a stand-alone style.
static TextStyle	valueOf(String name)	Returns the enum constant of this type with the specified name.
static TextStyle[]	values()	Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

clone, compareTo, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Enum Constant Detail

FULL

```
public static final TextStyle FULL
```

Full text, typically the full description. For example, day-of-week Monday might output "Monday".

FULL_STANDALONE

```
public static final TextStyle FULL_STANDALONE
```

Full text for stand-alone use, typically the full description. For example, day-of-week Monday might output "Monday".

SHORT

```
public static final TextStyle SHORT
```

Short text, typically an abbreviation. For example, day-of-week Monday might output "Mon".

SHORT_STANDALONE

```
public static final TextStyle SHORT_STANDALONE
```

Short text for stand-alone use, typically an abbreviation. For example, day-of-week Monday might output "Mon".

NARROW

```
public static final TextStyle NARROW
```

Narrow text, typically a single letter. For example, day-of-week Monday might output "M".

NARROW_STANDALONE

```
public static final TextStyle NARROW_STANDALONE
```

Narrow text for stand-alone use, typically a single letter. For example, day-of-week Monday might output "M".

Method Detail

values

```
public static TextStyle[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (TextStyle c : TextStyle.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static TextStyle valueOf(String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

IllegalArgumentException - if this enum type has no constant with the specified name

NullPointerException - if the argument is null

isStandalone

```
public boolean isStandalone()
```

Returns true if the Style is a stand-alone style.

Returns:

`true if the style is a stand-alone style.`

asStandalone

```
public TextStyle asStandalone()
```

Returns the stand-alone style with the same size.

Returns:

`the stand-alone style with the same size`

asNormal

```
public TextStyle asNormal()
```

Returns the normal style with the same size.

Returns:

`the normal style with the same size`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.