JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class AbstractMap.SimpleEntry<K,V>

java.lang.Object
    java.util.AbstractMap.SimpleEntry<K,V>

All Implemented Interfaces:

`Serializable, Map.Entry<K,V>`

Enclosing class:

`AbstractMap<K,V>`

```
public static class AbstractMap.SimpleEntry<K,V>
extends Object
implements Map.Entry<K,V>, Serializable
```

An Entry maintaining a key and a value. The value may be changed using the `setValue` method. This class facilitates the process of building custom map implementations. For example, it may be convenient to return arrays of `SimpleEntry` instances in method `Map.entrySet().toArray`.

Since:

1.6

See Also:

`Serialized Form`

Constructor Summary

Constructors

Constructor	Description
`SimpleEntry(K key, V value)`	Creates an entry

	representing a mapping from the specified key to the specified value.
`SimpleEntry(Map.Entry<? extends K,? extends V> entry)`	Creates an entry representing the same mapping as the specified entry.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
boolean	`equals(Object o)`	Compares the specified object with this entry for equality.
`K`	`getKey()`	Returns the key corresponding to this entry.
`V`	`getValue()`	Returns the value corresponding to this entry.
int	`hashCode()`	Returns the hash code value for this map entry.
`V`	`setValue(V value)`	Replaces the value corresponding to this entry with the specified value.
`String`	`toString()`	Returns a String representation of this map entry.

Methods inherited from class java.lang.Object

`clone`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Methods inherited from interface java.util.Map.Entry

comparingByKey, comparingByKey, comparingByValue, comparingByValue

Constructor Detail

SimpleEntry

```
public SimpleEntry(K key,
                   V value)
```

Creates an entry representing a mapping from the specified key to the specified value.

Parameters:

key - the key represented by this entry

value - the value represented by this entry

SimpleEntry

```
public SimpleEntry(Map.Entry<? extends K,? extends V> entry)
```

Creates an entry representing the same mapping as the specified entry.

Parameters:

entry - the entry to copy

Method Detail

getKey

```
public K getKey()
```

Returns the key corresponding to this entry.

Specified by:

getKey in interface Map.Entry<K,V>

Returns:

the key corresponding to this entry

getValue

```
public V getValue()
```

Returns the value corresponding to this entry.

Specified by:

`getValue` in interface `Map.Entry<K,V>`

Returns:

the value corresponding to this entry

setValue

```
public V setValue(V value)
```

Replaces the value corresponding to this entry with the specified value.

Specified by:

`setValue` in interface `Map.Entry<K,V>`

Parameters:

`value` - new value to be stored in this entry

Returns:

the old value corresponding to the entry

equals

```
public boolean equals(Object o)
```

Compares the specified object with this entry for equality. Returns `true` if the given object is also a map entry and the two entries represent the same mapping. More formally, two entries `e1` and `e2` represent the same mapping if

```
(e1.getKey()==null ?
 e2.getKey()==null :
 e1.getKey().equals(e2.getKey()))
&&
(e1.getValue()==null ?
 e2.getValue()==null :
 e1.getValue().equals(e2.getValue()))
```

This ensures that the `equals` method works properly across different implementations of the `Map.Entry` interface.

Specified by:

`equals` in interface `Map.Entry<K,V>`

Overrides:

`equals` in class `Object`

Parameters:

`o - object to be compared for equality with this map entry`

Returns:

`true if the specified object is equal to this map entry`

See Also:

`hashCode()`

hashCode

```
public int hashCode()
```

Returns
the hash code value for this map entry. The hash code of a map entry `e` is defined to be:

```
(e.getKey()==null   ? 0 : e.getKey().hashCode()) ^
(e.getValue()==null ? 0 : e.getValue().hashCode())
```

This ensures that `e1.equals(e2)` implies that `e1.hashCode()==e2.hashCode()` for any two Entries `e1` and `e2`, as required by the general contract of `Object.hashCode()`.

Specified by:

`hashCode` in interface `Map.Entry<K,V>`

Overrides:

`hashCode` in class `Object`

Returns:

`the hash code value for this map entry`

See Also:

`equals(java.lang.Object)`

toString

```
public String toString()
```

Returns a String representation of this map entry. This implementation returns the string representation of this entry's key followed by the equals character ("=") followed by the string representation of this entry's value.

Overrides:

`toString` in class `Object`

Returns:

```
a String representation of this map entry
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.