compact1, compact2, compact3

java.util

Class AbstractMap.SimpleImmutableEntry<K,V>

java.lang.Object
  java.util.AbstractMap.SimpleImmutableEntry<K,V>

All Implemented Interfaces:

Serializable, Map.Entry<K,V>

Enclosing class:

AbstractMap<K,V>

```
public static class AbstractMap.SimpleImmutableEntry<K,V>
extends Object
implements Map.Entry<K,V>, Serializable
```

An Entry maintaining an immutable key and value. This class does not support method `setValue`. This class may be convenient in methods that return thread-safe snapshots of key-value mappings.

Since:

1.6

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`SimpleImmutableEntry(K key, V value)`	Creates an entry representing

	a mapping from the specified key to the specified value.

`SimpleImmutableEntry(Map.Entry<? extends K,? extends V> entry)`	Creates an entry representing the same mapping as the specified entry.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
boolean	`equals(Object o)`	Compares the specified object with this entry for equality.
`K`	`getKey()`	Returns the key corresponding to this entry.
`V`	`getValue()`	Returns the value corresponding to this entry.
int	`hashCode()`	Returns the hash code value for this map entry.
`V`	`setValue(V value)`	Replaces the value corresponding to this entry with the specified value (optional operation).
`String`	`toString()`	Returns a String representation of this map entry.

Methods inherited from class java.lang.Object

`clone`, `finalize`, `getClass`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Methods inherited from interface java.util.Map.Entry

`comparingByKey`, `comparingByKey`, `comparingByValue`, `comparingByValue`

Constructor Detail

SimpleImmutableEntry

```
public SimpleImmutableEntry(K key,
                            V value)
```

Creates an entry representing a mapping from the specified key to the specified value.

Parameters:

`key - the key represented by this entry`

`value - the value represented by this entry`

SimpleImmutableEntry

```
public SimpleImmutableEntry(Map.Entry<? extends K,? extends V> entry)
```

Creates an entry representing the same mapping as the specified entry.

Parameters:

`entry - the entry to copy`

Method Detail

getKey

```
public K getKey()
```

Returns the key corresponding to this entry.

Specified by:

`getKey in interface Map.Entry<K,V>`

Returns:

`the key corresponding to this entry`

getValue

```
public V getValue()
```

Returns the value corresponding to this entry.

Specified by:

getValue in interface Map.Entry<K,V>

Returns:

the value corresponding to this entry

setValue

public V setValue(V value)

Replaces the value corresponding to this entry with the specified value (optional operation). This implementation simply throws UnsupportedOperationException, as this class implements an *immutable* map entry.

Specified by:

setValue in interface Map.Entry<K,V>

Parameters:

value - new value to be stored in this entry

Returns:

(Does not return)

Throws:

UnsupportedOperationException - always

equals

public boolean equals(Object o)

Compares the specified object with this entry for equality. Returns true if the given object is also a map entry and the two entries represent the same mapping. More formally, two entries e1 and e2 represent the same mapping if

```
(e1.getKey()==null ?
 e2.getKey()==null :
 e1.getKey().equals(e2.getKey()))
&&
(e1.getValue()==null ?
 e2.getValue()==null :
 e1.getValue().equals(e2.getValue()))
```

This ensures that the equals method works properly across different implementations of the Map.Entry interface.

Specified by:

equals in interface Map.Entry<K,V>

Overrides:

equals in class Object

Parameters:

o - object to be compared for equality with this map entry

Returns:

true if the specified object is equal to this map entry

See Also:

hashCode()

hashCode

```
public int hashCode()
```

Returns
the hash code value for this map entry. The hash code of a map entry e is defined to be:

```
(e.getKey()==null   ? 0 : e.getKey().hashCode()) ^
(e.getValue()==null ? 0 : e.getValue().hashCode())
```

This ensures that e1.equals(e2) implies that e1.hashCode()==e2.hashCode() for any two Entries e1 and e2, as required by the general contract of Object.hashCode().

Specified by:

hashCode in interface Map.Entry<K,V>

Overrides:

hashCode in class Object

Returns:

the hash code value for this map entry

See Also:

equals(java.lang.Object)

toString

```
public String toString()
```

Returns a String representation of this map entry. This implementation returns the string representation of this entry's key followed by the equals character ("=") followed by the string representation of this entry's value.

Overrides:

`toString` in class `Object`

Returns:

a String representation of this map entry

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.