JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class Base64.Decoder

java.lang.Object
    java.util.Base64.Decoder

Enclosing class:

Base64

```
public static class Base64.Decoder
extends Object
```

This class implements a decoder for decoding byte data using the Base64 encoding scheme as specified in RFC 4648 and RFC 2045.

The Base64 padding character `'='` is accepted and interpreted as the end of the encoded byte data, but is not required. So if the final unit of the encoded byte data only has two or three Base64 characters (without the corresponding padding character(s) padded), they are decoded as if followed by padding character(s). If there is a padding character present in the final unit, the correct number of padding character(s) must be present, otherwise `IllegalArgumentException` (`IOException` when reading from a Base64 stream) is thrown during decoding.

Instances of `Base64.Decoder` class are safe for use by multiple concurrent threads.

Unless otherwise noted, passing a `null` argument to a method of this class will cause a `NullPointerException` to be thrown.

Since:

1.8

See Also:

`Base64.Encoder`

Method Summary

Concrete Methods

Modifier and Type	Method	Description
byte[]	**decode**(byte[] src)	Decodes all bytes from the input byte array using the **Base64** encoding scheme, writing the results into a newly-allocated output byte array.
int	**decode**(byte[] src, byte[] dst)	Decodes all bytes from the input byte array using the **Base64** encoding scheme, writing the results into the given output byte array, starting at offset 0.
ByteBuffer	**decode**(**ByteBuffer** buffer)	Decodes all bytes from the input byte buffer using the **Base64** encoding scheme, writing the results into a newly-allocated ByteBuffer.
byte[]	**decode**(**String** src)	Decodes a Base64 encoded String into a newly-allocated byte array using the **Base64** encoding scheme.
InputStream	**wrap**(**InputStream** is)	Returns an input stream for decoding **Base64** encoded byte stream.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Method Detail

decode

```
public byte[] decode(byte[] src)
```

Decodes all bytes from the input byte array using the Base64 encoding scheme, writing the results into a newly-allocated output byte array. The returned byte array is of the length of the resulting bytes.

Parameters:

`src - the byte array to decode`

Returns:

`A newly-allocated byte array containing the decoded bytes.`

Throws:

`IllegalArgumentException - if src is not in valid Base64 scheme`

decode

```
public byte[] decode(String src)
```

Decodes
a Base64 encoded String into a newly-allocated byte array using the Base64 encoding scheme.

An invocation of this method has exactly the same effect as invoking `decode(src.getBytes(StandardCharsets.ISO_8859_1))`

Parameters:

`src - the string to decode`

Returns:

`A newly-allocated byte array containing the decoded bytes.`

Throws:

`IllegalArgumentException - if src is not in valid Base64 scheme`

decode

```
public int decode(byte[] src,
                  byte[] dst)
```

Decodes all bytes from the input byte array using the Base64 encoding scheme, writing the results into the given output byte array, starting at offset 0.

It is the responsibility of the invoker of this method to make sure the output byte array `dst` has enough space for decoding all bytes from the input byte array. No bytes will be be written to the output byte array if the output byte array is not big enough.

If the input byte array is not in valid Base64 encoding scheme then some bytes may have been written to the output byte array before IllegalargumentException is thrown.

Parameters:

`src - the byte array to decode`

`dst - the output byte array`

Returns:

`The number of bytes written to the output byte array`

Throws:

`IllegalArgumentException - if src is not in valid Base64 scheme, or dst does not have enough space for decoding all input bytes.`

decode

`public ByteBuffer decode(ByteBuffer buffer)`

Decodes all bytes from the input byte buffer using the `Base64` encoding scheme, writing the results into a newly-allocated ByteBuffer.

Upon return, the source buffer's position will be updated to its limit; its limit will not have been changed. The returned output buffer's position will be zero and its limit will be the number of resulting decoded bytes

`IllegalArgumentException` is thrown if the input buffer is not in valid Base64 encoding scheme. The position of the input buffer will not be advanced in this case.

Parameters:

`buffer - the ByteBuffer to decode`

Returns:

`A newly-allocated byte buffer containing the decoded bytes`

Throws:

`IllegalArgumentException - if src is not in valid Base64 scheme.`

wrap

`public InputStream wrap(InputStream is)`

Returns an input stream for decoding `Base64` encoded byte stream.

The `read` methods of the returned `InputStream` will throw `IOException` when reading bytes that cannot be decoded.

Closing the returned input stream will close the underlying input stream.

Parameters:

`is - the input stream`

Returns:

`the input stream for decoding the specified Base64 encoded byte stream`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.