JavaScript is disabled on your browser.

Class EventListenerProxy<T extends EventListener>

java.lang.Object
    java.util.EventListenerProxy<T>

All Implemented Interfaces:

EventListener

Direct Known Subclasses:

AWTEventListenerProxy, PropertyChangeListenerProxy, VetoableChangeListenerProxy

---

```
public abstract class EventListenerProxy<T extends EventListener>
extends Object
implements EventListener
```

An abstract wrapper class for an `EventListener` class which associates a set of additional parameters with the listener. Subclasses must provide the storage and accessor methods for the additional arguments or parameters.

For example, a bean which supports named properties would have a two argument method signature for adding a `PropertyChangeListener` for a property:

```
public void addPropertyChangeListener(String propertyName,
                                      PropertyChangeListener listener)
```

If the bean also implemented the zero argument get listener method:

```
public PropertyChangeListener[] getPropertyChangeListeners()
```

then the array may contain inner `PropertyChangeListeners` which are also `PropertyChangeListenerProxy` objects.

If the calling method is interested in retrieving the named property then it would have to test the element to see if it is a proxy class.

Since:

1.4

Constructor Summary

Constructors

Constructor	Description
`EventListenerProxy(T listener)`	Creates a proxy for the specified listener.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`T`	`getListener()`	Returns the listener associated with the proxy.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

EventListenerProxy

```
public EventListenerProxy(T listener)
```

Creates a proxy for the specified listener.

Parameters:

`listener - the listener object`

Method Detail

getListener

```
public T getListener()
```

Returns the listener associated with the proxy.

Returns:

`the listener associated with the proxy`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.