JavaScript is disabled on your browser.



compact1, compact2, compact3

java.util

# Class EventObject

java.lang.Object
    java.util.EventObject

**All Implemented Interfaces:**

Serializable

**Direct Known Subclasses:**

AWTEvent, BeanContextEvent, CaretEvent, ChangeEvent, ConnectionEvent, DragGestureEvent, DragSourceEvent, DropTargetEvent, FlavorEvent, HandshakeCompletedEvent, HyperlinkEvent, LineEvent, ListDataEvent, ListSelectionEvent, MenuEvent, NamingEvent, NamingExceptionEvent, NodeChangeEvent, Notification, PopupMenuEvent, PreferenceChangeEvent, PrintEvent, PropertyChangeEvent, RowSetEvent, RowSorterEvent, SSLSessionBindingEvent, StatementEvent, TableColumnModelEvent, TableModelEvent, TreeExpansionEvent, TreeModelEvent, TreeSelectionEvent, UndoableEditEvent, UnsolicitedNotificationEvent

---

```
public class EventObject
extends Object
implements Serializable
```

The root class from which all event state objects shall be derived.

All Events are constructed with a reference to the object, the "source", that is logically deemed to be the object upon which the Event in question initially occurred upon.

**Since:**

JDK1.1

**See Also:**

Serialized Form

## Field Summary

**Fields**

| Modifier and Type | Field | Description |
|---|---|---|
| protected `Object` | `source` | The object on which the Event initially occurred. |

## Constructor Summary

**Constructors**

| Constructor | Description |
|---|---|
| `EventObject(Object source)` | Constructs a prototypical Event. |

## Method Summary

**Concrete Methods**

| Modifier and Type | Method | Description |
|---|---|---|
| `Object` | `getSource()` | The object on which the Event initially occurred. |
| `String` | `toString()` | Returns a String representation of this EventObject. |

### Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

## Field Detail

### source

```
protected transient Object source
```

The object on which the Event initially occurred.

## *Constructor Detail*

### EventObject

```
public EventObject(Object source)
```

Constructs a prototypical Event.

**Parameters:**

`source - The object on which the Event initially occurred.`

**Throws:**

`IllegalArgumentException - if source is null.`

## *Method Detail*

### getSource

```
public Object getSource()
```

The object on which the Event initially occurred.

**Returns:**

`The object on which the Event initially occurred.`

### toString

```
public String toString()
```

Returns a String representation of this EventObject.

**Overrides:**

`toString in class Object`

**Returns:**

```
A a String representation of this EventObject.
```



Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.