JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class FormatFlagsConversionMismatchException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalArgumentException
          java.util.IllegalFormatException
            java.util.FormatFlagsConversionMismatchException

All Implemented Interfaces:

Serializable

```
public class FormatFlagsConversionMismatchException
extends IllegalFormatException
```

Unchecked exception thrown when a conversion and flag are incompatible.

Unless otherwise specified, passing a `null` argument to any method or constructor in this class will cause a `NullPointerException` to be thrown.

Since:

1.5

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`FormatFlagsConversionMismatchException(String f, char c)`	

	Constructs an instance of this class with the specified flag and conversion.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
char	**getConversion**()	Returns the incompatible conversion.
String	**getFlags**()	Returns the incompatible flag.
String	**getMessage**()	Returns the detail message string of this throwable.

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

FormatFlagsConversionMismatchException

```
public FormatFlagsConversionMismatchException(String f,
                                              char c)
```

Constructs an instance of this class with the specified flag and conversion.

Parameters:

f - The flag

c - The conversion

Method Detail

getFlags

```
public String getFlags()
```

Returns the incompatible flag.

Returns:

The flag

getConversion

```
public char getConversion()
```

Returns the incompatible conversion.

Returns:

The conversion

getMessage

```
public String getMessage()
```

Description copied from class: Throwable

Returns the detail message string of this throwable.

Overrides:

getMessage in class Throwable

Returns:

the detail message string of this Throwable instance (which may be null).

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.