JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class FormatterClosedException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalStateException
          java.util.FormatterClosedException

All Implemented Interfaces:

Serializable

```
public class FormatterClosedException
extends IllegalStateException
```

Unchecked exception thrown when the formatter has been closed.

Unless otherwise specified, passing a `null` argument to any method or constructor in this class will cause a `NullPointerException` to be thrown.

Since:

1.5

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
FormatterClosedException()	Constructs an instance of this class.

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

FormatterClosedException

```
public FormatterClosedException()
```

Constructs an instance of this class.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.