JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class IllegalFormatCodePointException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalArgumentException
          java.util.IllegalFormatException
            java.util.IllegalFormatCodePointException

All Implemented Interfaces:

Serializable

```
public class IllegalFormatCodePointException
extends IllegalFormatException
```

Unchecked exception thrown when a character with an invalid Unicode code point as defined by `Character.isValidCodePoint(int)` is passed to the `Formatter`.

Unless otherwise specified, passing a `null` argument to any method or constructor in this class will cause a `NullPointerException` to be thrown.

Since:

1.5

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description

IllegalFormatCodePointException(int c)	Constructs an instance of this class with the specified illegal code point as defined by **Character.isValidCodePoint(int)**.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
int	**getCodePoint**()	Returns the illegal code point as defined by **Character.isValidCodePoint(int)**.
String	**getMessage**()	Returns the detail message string of this throwable.

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

IllegalFormatCodePointException

```
public IllegalFormatCodePointException(int c)
```

Constructs an instance of this class with the specified illegal code point as defined by Character.isValidCodePoint(int).

Parameters:

c - The illegal Unicode code point

Method Detail

getCodePoint

```
public int getCodePoint()
```

Returns the illegal code point as defined by `Character.isValidCodePoint(int)`.

Returns:

The illegal Unicode code point

getMessage

```
public String getMessage()
```

Description copied from class: `Throwable`

Returns the detail message string of this throwable.

Overrides:

`getMessage` in class `Throwable`

Returns:

the detail message string of this Throwable instance (which may be null).

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.