JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class IllegalFormatConversionException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalArgumentException
          java.util.IllegalFormatException
            java.util.IllegalFormatConversionException

All Implemented Interfaces:

Serializable

```
public class IllegalFormatConversionException
extends IllegalFormatException
```

Unchecked exception thrown when the argument corresponding to the format specifier is of an incompatible type.

Unless otherwise specified, passing a `null` argument to any method or constructor in this class will cause a `NullPointerException` to be thrown.

Since:

1.5

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description

`IllegalFormatConversionException(char c, Class<?> arg)`	Constructs an instance of this class with the mismatched conversion and the corresponding argument class.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`Class<?>`	`getArgumentClass()`	Returns the class of the mismatched argument.
`char`	`getConversion()`	Returns the inapplicable conversion.
`String`	`getMessage()`	Returns the detail message string of this throwable.

Methods inherited from class java.lang.Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Detail

IllegalFormatConversionException

```
public IllegalFormatConversionException(char c,
                                        Class<?> arg)
```

Constructs an instance of this class with the mismatched conversion and the corresponding argument class.

Parameters:

`c - Inapplicable conversion`

`arg - Class of the mismatched argument`

Method Detail

getConversion

```
public char getConversion()
```

Returns the inapplicable conversion.

Returns:

`The inapplicable conversion`

getArgumentClass

```
public Class<?> getArgumentClass()
```

Returns the class of the mismatched argument.

Returns:

`The class of the mismatched argument`

getMessage

```
public String getMessage()
```

Description copied from class: `Throwable`
Returns the detail message string of this throwable.

Overrides:

`getMessage` in class `Throwable`

Returns:

C

```
the detail message string of this Throwable instance (which may be
null).
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.