JavaScript is disabled on your browser.



compact1, compact2, compact3

java.util

# Class IllformedLocaleException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.util.IllformedLocaleException

**All Implemented Interfaces:**

Serializable

---

```
public class IllformedLocaleException
extends RuntimeException
```

Thrown by methods in `Locale` and `Locale.Builder` to indicate that an argument is not a well-formed BCP 47 tag.

**Since:**

1.7

**See Also:**

`Locale`, `Serialized Form`

## *Constructor Summary*

**Constructors**

| Constructor | Description |
| --- | --- |
| `IllformedLocaleException()` | Constructs a new `IllformedLocaleExceptio` with no detail message and -1 as the error index. |

| | |
|---|---|
| `IllformedLocaleException(String message)` | Constructs a new `IllformedLocaleExceptio` with the given message an -1 as the error index. |
| `IllformedLocaleException(String message, int errorIndex)` | Constructs a new `IllformedLocaleExceptio` with the given message an the error index. |

## *Method Summary*

**Concrete Methods**

| Modifier and Type | Method | Description |
|---|---|---|
| `int` | `getErrorIndex()` | Returns the index where the error was found. |

### Methods inherited from class java.lang.Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

### Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

## *Constructor Detail*

### IllformedLocaleException

```
public IllformedLocaleException()
```

Constructs a new `IllformedLocaleException` with no detail message and -1 as the error index.

### IllformedLocaleException

```
public IllformedLocaleException(String message)
```

Constructs a new `IllformedLocaleException` with the given message and -1 as the error index.

**Parameters:**

`message - the message`

### IllformedLocaleException

```
public IllformedLocaleException(String message,
                                int errorIndex)
```

Constructs a new `IllformedLocaleException` with the given message and the error index. The error index is the approximate offset from the start of the ill-formed value to the point where the parse first detected an error. A negative error index value indicates either the error index is not applicable or unknown.

**Parameters:**

`message - the message`

`errorIndex - the index`

## *Method Detail*

### getErrorIndex

```
public int getErrorIndex()
```

Returns the index where the error was found. A negative value indicates either the error index is not applicable or unknown.

**Returns:**

```
the error index
```



Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.