JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class ListResourceBundle

java.lang.Object
    java.util.ResourceBundle
        java.util.ListResourceBundle

Direct Known Subclasses:

AccessibleResourceBundle

```
public abstract class ListResourceBundle
extends ResourceBundle
```

`ListResourceBundle` is an abstract subclass of `ResourceBundle` that manages resources for a locale in a convenient and easy to use list. See `ResourceBundle` for more information about resource bundles in general.

Subclasses must override `getContents` and provide an array, where each item in the array is a pair of objects. The first element of each pair is the key, which must be a `String`, and the second element is the value associated with that key.

The following example shows two members of a resource bundle family with the base name "MyResources". "MyResources" is the default member of the bundle family, and "MyResources_fr" is the French member. These members are based on `ListResourceBundle` (a related example shows how you can add a bundle to this family that's based on a properties file). The keys in this example are of the form "s1" etc. The actual keys are entirely up to your choice, so long as they are the same as the keys you use in your program to retrieve the objects from the bundle. Keys are case-sensitive.

```
public class MyResources extends ListResourceBundle {
    protected Object[][] getContents() {
        return new Object[][] {
        // LOCALIZE THIS
            {"s1", "The disk \"{1}\" contains {0}."},  // MessageFormat patte
```

```
            {"s2", "1"},                                // location of {0} in
            {"s3", "My Disk"},                          // sample disk name
            {"s4", "no files"},                         // first ChoiceFormat
            {"s5", "one file"},                         // second ChoiceFormat
            {"s6", "{0,number} files"},                 // third ChoiceFormat
            {"s7", "3 Mar 96"},                         // sample date
            {"s8", new Dimension(1,5)}                  // real object, not ju
        // END OF MATERIAL TO LOCALIZE
        };
    }
}

public class MyResources_fr extends ListResourceBundle {
    protected Object[][] getContents() {
        return new Object[][] {
        // LOCALIZE THIS
            {"s1", "Le disque \"{1}\" {0}."},           // MessageFormat patte
            {"s2", "1"},                                // location of {0} in
            {"s3", "Mon disque"},                       // sample disk name
            {"s4", "ne contient pas de fichiers"},      // first ChoiceFormat
            {"s5", "contient un fichier"},              // second ChoiceFormat
            {"s6", "contient {0,number} fichiers"},     // third ChoiceFormat
            {"s7", "3 mars 1996"},                      // sample date
            {"s8", new Dimension(1,3)}                  // real object, not ju
        // END OF MATERIAL TO LOCALIZE
        };
    }
}
```

The implementation of a `ListResourceBundle` subclass must be thread-safe if it's simultaneously used by multiple threads. The default implementations of the methods in this class are thread-safe.

Since:

JDK1.1

See Also:

`ResourceBundle`, `PropertyResourceBundle`

Nested Class Summary

Nested classes/interfaces inherited from class java.util.ResourceBundle

`ResourceBundle.Control`

Field Summary

Fields inherited from class java.util.ResourceBundle

parent

Constructor Summary

Constructors

Constructor	Description
ListResourceBundle()	Sole constructor.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
protected abstract Object[][]	getContents()	Returns an array in which each item is a pair of objects in an Object array.
Enumeration<String>	getKeys()	Returns an Enumeration of the keys contained in this ResourceBundle and its parent bundles.
Object	handleGetObject(String key)	Gets an object for the given key from this resource bundle.
protected Set<String>	handleKeySet()	Returns a Set of the keys contained *only* in this ResourceBundle.

Methods inherited from class java.util.ResourceBundle

clearCache, clearCache, containsKey, getBaseBundleName, getBundle, getBundle, getBundle, getBundle, getBundle, getBundle, getLocale, getObject, getString, getStringArray, keySet, setParent

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

ListResourceBundle

```
public ListResourceBundle()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Detail

handleGetObject

```
public final Object handleGetObject(String key)
```

Description copied from class: ResourceBundle

Gets an object for the given key from this resource bundle. Returns null if this resource bundle does not contain an object for the given key.

Specified by:

handleGetObject in class ResourceBundle

Parameters:

key - the key for the desired object

Returns:

the object for the given key, or null

getKeys

```
public Enumeration<String> getKeys()
```

Returns an `Enumeration` of the keys contained in this `ResourceBundle` and its parent bundles.

Specified by:

`getKeys` in class `ResourceBundle`

Returns:

an `Enumeration` of the keys contained in this `ResourceBundle` and its parent bundles.

See Also:

`ResourceBundle.keySet()`

handleKeySet

```
protected Set<String> handleKeySet()
```

Returns a `Set` of the keys contained *only* in this `ResourceBundle`.

Overrides:

`handleKeySet` in class `ResourceBundle`

Returns:

a `Set` of the keys contained only in this `ResourceBundle`

Since:

1.6

See Also:

`ResourceBundle.keySet()`

getContents

```
protected abstract Object[][] getContents()
```

Returns an array in which each item is a pair of objects in an `Object` array. The first element of each pair is the key, which must be a `String`, and the second element is the value associated with that key. See the class description for details.

Returns:

```
an array of an Object array representing a key-value pair.
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.