JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Enum Locale.Category

java.lang.Object
    java.lang.Enum<Locale.Category>
        java.util.Locale.Category

All Implemented Interfaces:

Serializable, Comparable<Locale.Category>

Enclosing class:

Locale

```
public static enum Locale.Category
extends Enum<Locale.Category>
```

Enum for locale categories. These locale categories are used to get/set the default locale for the specific functionality represented by the category.

Since:

1.7

See Also:

Locale.getDefault(Locale.Category), Locale.setDefault(Locale.Category, Locale)

Enum Constant Summary

Enum Constants

Enum Constant	Description
DISPLAY	Category used to represent the default locale for displaying user interfaces.

FORMAT	Category used to represent the default locale for formatting dates, numbers, and/or currencies.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
static Locale.Category	valueOf(String name)	Returns the enum constant of this type with the specified name.
static Locale.Category[]	values()	Returns an array containing the constants of this enum type, in the order they are declared.

Methods inherited from class java.lang.Enum

clone, compareTo, equals, finalize, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object

getClass, notify, notifyAll, wait, wait, wait

Enum Constant Detail

DISPLAY

```
public static final Locale.Category DISPLAY
```

Category used to represent the default locale for displaying user interfaces.

FORMAT

```
public static final Locale.Category FORMAT
```

Category used to represent the default locale for formatting dates, numbers, and/or currencies.

Method Detail

values

```
public static Locale.Category[] values()
```

Returns an array containing the constants of this enum type, in the order they are declared. This method may be used to iterate over the constants as follows:

```
for (Locale.Category c : Locale.Category.values())
    System.out.println(c);
```

Returns:

an array containing the constants of this enum type, in the order they are declared

valueOf

```
public static Locale.Category valueOf(String name)
```

Returns the enum constant of this type with the specified name. The string must match *exactly* an identifier used to declare an enum constant in this type. (Extraneous whitespace characters are not permitted.)

Parameters:

name - the name of the enum constant to be returned.

Returns:

the enum constant with the specified name

Throws:

IllegalArgumentException - if this enum type has no constant with the specified name

`NullPointerException` - if the argument is null

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.