JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class Locale.LanguageRange

java.lang.Object
    java.util.Locale.LanguageRange

Enclosing class:

Locale

```
public static final class Locale.LanguageRange
extends Object
```

This class expresses a *Language Range* defined in RFC 4647 Matching of Language Tags. A language range is an identifier which is used to select language tag(s) meeting specific requirements by using the mechanisms described in Locale Matching. A list which represents a user's preferences and consists of language ranges is called a *Language Priority List*.

There are two types of language ranges: basic and extended. In RFC 4647, the syntax of language ranges is expressed in ABNF as follows:

```
basic-language-range    = (1*8ALPHA *("-" 1*8alphanum)) / "*"
extended-language-range = (1*8ALPHA / "*")
                          *("-" (1*8alphanum / "*"))
alphanum                = ALPHA / DIGIT
```

For example, `"en"` (English), `"ja-JP"` (Japanese, Japan), `"*"` (special language range which matches any language tag) are basic language ranges, whereas `"*-CH"` (any languages, Switzerland), `"es-*"` (Spanish, any regions), and `"zh-Hant-*"` (Traditional Chinese, any regions) are extended language ranges.

Since:

1.8

See Also:

Locale.filter(java.util.List<java.util.Locale.LanguageRange>, java.util.Collection<java.util.Locale>, java.util.Locale.FilteringMode), Locale.filterTags(java.util.List<java.util.Locale.LanguageRange>, java.util.Collection<java.lang.String>, java.util.Locale.FilteringMode), Locale.lookup(java.util.List<java.util.Locale.LanguageRange>, java.util.Collection<java.util.Locale>), Locale.lookupTag(java.util.List<java.util.Locale.LanguageRange>, java.util.Collection<java.lang.String>)

Field Summary

Fields

Modifier and Type	Field	Description
static double	MAX_WEIGHT	A constant holding the maximum value of weight, 1.0, which indicates that the language range is a good fit for the user.
static double	MIN_WEIGHT	A constant holding the minimum value of weight, 0.0, which indicates that the language range is not a good fit for the user.

Constructor Summary

Constructors

Constructor	Description
LanguageRange(String range)	Constructs a LanguageRange using the given range.
LanguageRange(String range, double weight)	Constructs a LanguageRange using the given range and weight.

Method Summary

Concrete Methods

Modifier and Type	Method
boolean	**equals**(**Object** obj)
String	**getRange**()
double	**getWeight**()
int	**hashCode**()
static **List**<**Locale.LanguageRange**>	**mapEquivalents**(**List**<**Locale.LanguageRange**> prio **Map**<**String**,**List**<**String**>> map)
static **List**<**Locale.LanguageRange**>	**parse**(**String** ranges)
static **List**<**Locale.LanguageRange**>	**parse**(**String** ranges, **Map**<**String**,**List**<**String**>>

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, toString, wait, wait, wait

Field Detail

MAX_WEIGHT

```
public static final double MAX_WEIGHT
```

A constant holding the maximum value of weight, 1.0, which indicates that the language range is a good fit for the user.

See Also:

Constant Field Values

MIN_WEIGHT

```
public static final double MIN_WEIGHT
```

A constant holding the minimum value of weight, 0.0, which indicates that the language range is not a good fit for the user.

See Also:

Constant Field Values

Constructor Detail

LanguageRange

```
public LanguageRange(String range)
```

Constructs a `LanguageRange` using the given `range`. Note that no validation is done against the IANA Language Subtag Registry at time of construction.

This is equivalent to `LanguageRange(range, MAX_WEIGHT)`.

Parameters:

`range` - a language range

Throws:

`NullPointerException` - if the given range is null

LanguageRange

```
public LanguageRange(String range,
                     double weight)
```

Constructs a LanguageRange using the given range and weight. Note that no validation is done against the IANA Language Subtag Registry at time of construction.

Parameters:

range - a language range

weight - a weight value between MIN_WEIGHT and MAX_WEIGHT

Throws:

NullPointerException - if the given range is null

IllegalArgumentException - if the given weight is less than MIN_WEIGHT or greater than MAX_WEIGHT

Method Detail

getRange

```
public String getRange()
```

Returns the language range of this LanguageRange.

Returns:

the language range.

getWeight

```
public double getWeight()
```

Returns the weight of this LanguageRange.

Returns:

the weight value.

parse

```
public static List<Locale.LanguageRange> parse(String ranges)
```

Parses the given ranges to generate a Language Priority List.

This
method performs a syntactic check for each language range in the given `ranges` but doesn't do validation using the IANA Language Subtag Registry.

The `ranges` to be given can take one of the following forms:

```
"Accept-Language: ja,en;q=0.4"  (weighted list with Accept-Language prefix)
"ja,en;q=0.4"                   (weighted list)
"ja,en"                         (prioritized list)
```

In a weighted list, each language range is given a weight value. The weight value is identical to the "quality value" in RFC 2616, and it expresses how much the user prefers the language. A weight value is specified after a corresponding language range followed by `";q="`, and the default weight value is `MAX_WEIGHT` when it is omitted.

Unlike a weighted list, language ranges in a prioritized list are sorted in the descending order based on its priority. The first language range has the highest priority and meets the user's preference most.

In either case, language ranges are sorted in descending order in the Language Priority List based on priority or weight. If a language range appears in the given `ranges` more than once, only the first one is included on the Language Priority List.

The returned list consists of language ranges from the given `ranges` and their equivalents found in the IANA Language Subtag Registry. For example, if the given `ranges` is `"Accept-Language: iw,en-us;q=0.7,en;q=0.3"`, the elements in the list to be returned are:

Range	**Weight**
"iw" (older tag for Hebrew)	1.0
"he" (new preferred code for Hebrew)	1.0
"en-us" (English, United States)	0.7
"en" (English)	0.3

Two language ranges, `"iw"` and `"he"`, have the same highest priority in the list. By adding `"he"` to the user's Language Priority List, locale-matching method can find Hebrew as a matching locale (or language tag) even if the application or system offers only `"he"` as a supported locale (or language tag).

Parameters:

`ranges - a list of comma-separated language ranges or a list of language ranges in the form of the "Accept-Language" header defined in RFC 2616`

Returns:

a Language Priority List consisting of language ranges included in the given ranges and their equivalent language ranges if available. The list is modifiable.

Throws:

NullPointerException - if ranges is null

IllegalArgumentException - if a language range or a weight found in the given ranges is ill-formed

parse

```
public static List<Locale.LanguageRange> parse(String ranges,
                                               Map<String,List<String>> map)
```

Parses the given ranges to generate a Language Priority List, and then customizes the list using the given map. This method is equivalent to mapEquivalents(parse(ranges), map).

Parameters:

ranges - a list of comma-separated language ranges or a list of language ranges in the form of the "Accept-Language" header defined in RFC 2616

map - a map containing information to customize language ranges

Returns:

a Language Priority List with customization. The list is modifiable.

Throws:

NullPointerException - if ranges is null

IllegalArgumentException - if a language range or a weight found in the given ranges is ill-formed

See Also:

parse(String), mapEquivalents(java.util.List<java.util.Locale.LanguageRange>, java.util.Map<java.lang.String, java.util.List<java.lang.String>>)

mapEquivalents

```
public static List<Locale.LanguageRange> mapEquivalents(List<Locale.LanguageRange
                                                         Map<String,List<String>>
```

Generates a new customized Language Priority List using the given priorityList and map. If the given map is empty, this method returns a copy of the given priorityList.

In the map, a key represents a language range whereas a value is a list of equivalents of it. '*' cannot be used in the map. Each equivalent language range has the same weight value as its original language range.

```
An example of map:
  Key                              Value
    "zh" (Chinese)                   "zh",
                                     "zh-Hans"(Simplified Chinese)
    "zh-HK" (Chinese, Hong Kong)     "zh-HK"
    "zh-TW" (Chinese, Taiwan)        "zh-TW"
```

The customization is performed after modification using the IANA Language Subtag Registry.

For example, if a user's Language Priority List consists of five language ranges ("zh", "zh-CN", "en", "zh-TW", and "zh-HK"), the newly generated Language Priority List which is customized using the above map example will consists of "zh", "zh-Hans", "zh-CN", "zh-Hans-CN", "en", "zh-TW", and "zh-HK".

"zh-HK" and "zh-TW" aren't converted to "zh-Hans-HK" nor "zh-Hans-TW" even if they are included in the Language Priority List. In this example, mapping is used to clearly distinguish Simplified Chinese and Traditional Chinese.

If the "zh"-to-"zh" mapping isn't included in the map, a simple replacement will be performed and the customized list won't include "zh" and "zh-CN".

Parameters:

priorityList - user's Language Priority List

map - a map containing information to customize language ranges

Returns:

a new Language Priority List with customization. The list is modifiable.

Throws:

NullPointerException - if priorityList is null

See Also:

parse(String, Map)

hashCode

```
public int hashCode()
```

Returns a hash code value for the object.

Overrides:

hashCode in class Object

Returns:

a hash code value for this object.

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

equals

```
public boolean equals(Object obj)
```

Compares this object to the specified object. The result is true if and only if the argument is not `null` and is a `LanguageRange` object that contains the same `range` and `weight` values as this object.

Overrides:

`equals` in class `Object`

Parameters:

`obj` - the object to compare with

Returns:

`true` if this object's range and weight are the same as the obj's; `false` otherwise.

See Also:

`Object.hashCode()`, `HashMap`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.