JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Interface PrimitiveIterator.OfInt

All Superinterfaces:

`Iterator<Integer>, PrimitiveIterator<Integer,IntConsumer>`

Enclosing interface:

`PrimitiveIterator<T,T_CONS>`

```
public static interface PrimitiveIterator.OfInt
extends PrimitiveIterator<Integer,IntConsumer>
```

An Iterator specialized for `int` values.

Since:

1.8

Nested Class Summary

Nested classes/interfaces inherited from interface java.util.PrimitiveIterator

`PrimitiveIterator.OfDouble, PrimitiveIterator.OfInt, PrimitiveIterator.OfLong`

Method Summary

Abstract Methods | **Default Methods**

Modifier and Type	Method	Description
default void	**forEachRemaining**(**Consumer**<? super **Integer**> action)	Performs the given action for each remaining element until all elements have been processed or the action throws an exception.
default void	**forEachRemaining**(**IntConsumer** action)	Performs the given action for each remaining element until all elements have been processed or the action throws an exception.
default **Integer**	**next**()	Returns the next element in the iteration.
int	**nextInt**()	Returns the next `int` element in the iteration.

Methods inherited from interface java.util.Iterator

hasNext, remove

Method Detail

nextInt

```
int nextInt()
```

Returns the next `int` element in the iteration.

Returns:

the next int element in the iteration

Throws:

`NoSuchElementException` - if the iteration has no more elements

forEachRemaining

```
default void forEachRemaining(IntConsumer action)
```

Performs the given action for each remaining element until all elements have been processed or the action throws an exception. Actions are performed in the order of iteration, if that order is specified. Exceptions thrown by the action are relayed to the caller.

Specified by:

`forEachRemaining` in
interface `PrimitiveIterator<Integer,IntConsumer>`

Implementation Requirements:

The default implementation behaves as if:

```
     while (hasNext())
         action.accept(nextInt());
```

Parameters:

action - The action to be performed for each element

Throws:

`NullPointerException` - if the specified action is null

next

```
default Integer next()
```

Returns the next element in the iteration.

Specified by:

next in interface Iterator<Integer>

Implementation Requirements:

The default implementation boxes the result of calling nextInt(), and returns that boxed result.

Returns:

the next element in the iteration

forEachRemaining

```
default void forEachRemaining(Consumer<? super Integer> action)
```

Performs the given action for each remaining element until all elements have been processed or the action throws an exception. Actions are performed in the order of iteration, if that order is specified. Exceptions thrown by the action are relayed to the caller.

Specified by:

forEachRemaining in interface Iterator<Integer>

Implementation Requirements:

If the action is an instance of IntConsumer then it is cast to IntConsumer and passed to forEachRemaining(java.util.function.IntConsumer); otherwise the action is adapted to an instance of IntConsumer, by boxing the argument of IntConsumer, and then passed to forEachRemaining(java.util.function.IntConsumer).

Parameters:

action - The action to be performed for each element

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.