JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Interface PrimitiveIterator.OfLong

All Superinterfaces:

`Iterator<Long>, PrimitiveIterator<Long,LongConsumer>`

Enclosing interface:

`PrimitiveIterator<T,T_CONS>`

```
public static interface PrimitiveIterator.OfLong
extends PrimitiveIterator<Long,LongConsumer>
```

An Iterator specialized for `long` values.

Since:

1.8

Nested Class Summary

Nested classes/interfaces inherited from interface java.util.PrimitiveIterator

`PrimitiveIterator.OfDouble, PrimitiveIterator.OfInt, PrimitiveIterator.OfLong`

Method Summary

Abstract Methods | Default Methods

Modifier and Type	Method	Description
default void	forEachRemaining(Consumer<? super Long> action)	Performs the given action for each remaining element until all elements have been processed or the action throws an exception.
default void	forEachRemaining(LongConsumer action)	Performs the given action for each remaining element until all elements have been processed or the action throws an exception.
default Long	next()	Returns the next element in the iteration.
long	nextLong()	Returns the next long element in the iteration.

Methods inherited from interface java.util.Iterator

hasNext, remove

Method Detail

nextLong

```
long nextLong()
```

Returns the next long element in the iteration.

Returns:

the next long element in the iteration

Throws:

NoSuchElementException - if the iteration has no more elements

forEachRemaining

```
default void forEachRemaining(LongConsumer action)
```

Performs the given action for each remaining element until all elements have been processed or the action throws an exception. Actions are performed in the order of iteration, if that order is specified. Exceptions thrown by the action are relayed to the caller.

Specified by:

forEachRemaining in interface PrimitiveIterator<Long,LongConsumer>

Implementation Requirements:

The default implementation behaves as if:

```
    while (hasNext())
        action.accept(nextLong());
```

Parameters:

action - The action to be performed for each element

Throws:

NullPointerException - if the specified action is null

next

```
default Long next()
```

Returns the next element in the iteration.

Specified by:

`next` in interface `Iterator<Long>`

Implementation Requirements:

The default implementation boxes the result of calling `nextLong()`, and returns that boxed result.

Returns:

the next element in the iteration

forEachRemaining

```
default void forEachRemaining(Consumer<? super Long> action)
```

Performs the given action for each remaining element until all elements have been processed or the action throws an exception. Actions are performed in the order of iteration, if that order is specified. Exceptions thrown by the action are relayed to the caller.

Specified by:

`forEachRemaining` in interface `Iterator<Long>`

Implementation Requirements:

If the action is an instance of LongConsumer then it is cast to LongConsumer and passed to `forEachRemaining(java.util.function.LongConsumer)`; otherwise the action is adapted to an instance of LongConsumer, by boxing the argument of LongConsumer, and then passed to `forEachRemaining(java.util.function.LongConsumer)`.

Parameters:

```
action - The action to be performed for each element
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.