compact1, compact2, compact3

java.util

Class PropertyResourceBundle

java.lang.Object
    java.util.ResourceBundle
        java.util.PropertyResourceBundle

```
public class PropertyResourceBundle
extends ResourceBundle
```

`PropertyResourceBundle` is a concrete subclass of `ResourceBundle` that manages resources for a locale using a set of static strings from a property file. See `ResourceBundle` for more information about resource bundles.

Unlike other types of resource bundle, you don't subclass `PropertyResourceBundle`. Instead, you supply properties files containing the resource data. `ResourceBundle.getBundle` will automatically look for the appropriate properties file and create a `PropertyResourceBundle` that refers to it. See `ResourceBundle.getBundle` for a complete description of the search and instantiation strategy.

The following example shows a member of a resource bundle family with the base name "MyResources". The text defines the bundle "MyResources_de", the German member of the bundle family. This member is based on `PropertyResourceBundle`, and the text therefore is the content of the file "MyResources_de.properties" (a related example shows how you can add bundles to this family that are implemented as subclasses of `ListResourceBundle`). The keys in this example are of the form "s1" etc. The actual keys are entirely up to your choice, so long as they are the same as the keys you use in your program to retrieve the objects from the bundle. Keys are case-sensitive.

```
# MessageFormat pattern
s1=Die Platte \"{1}\" enthält {0}.

# location of {0} in pattern
```

```
s2=1

# sample disk name
s3=Meine Platte

# first ChoiceFormat choice
s4=keine Dateien

# second ChoiceFormat choice
s5=eine Datei

# third ChoiceFormat choice
s6={0,number} Dateien

# sample date
s7=3. März 1996
```

The implementation of a `PropertyResourceBundle` subclass must be thread-safe if it's simultaneously used by multiple threads. The default implementations of the non-abstract methods in this class are thread-safe.

Note: PropertyResourceBundle can be constructed either from an InputStream or a Reader, which represents a property file. Constructing a PropertyResourceBundle instance from an InputStream requires that the input stream be encoded in ISO-8859-1. In that case, characters that cannot be represented in ISO-8859-1 encoding must be represented by Unicode Escapes as defined in section 3.3 of *The Java™ Language Specification* whereas the other constructor which takes a Reader does not have that limitation.

Since:

JDK1.1

See Also:

`ResourceBundle`, `ListResourceBundle`, `Properties`

Nested Class Summary

Nested classes/interfaces inherited from class java.util.ResourceBundle

`ResourceBundle.Control`

Field Summary

Fields inherited from class java.util.ResourceBundle

parent

Constructor Summary

Constructors

Constructor	Description
`PropertyResourceBundle(InputStream stream)`	Creates a property resource bundle from an `InputStream`.
`PropertyResourceBundle(Reader reader)`	Creates a property resource bundle from a `Reader`.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`Enumeration<String>`	`getKeys()`	Returns an `Enumeration` of the keys contained in this `ResourceBundle` and its parent bundles.
`Object`	`handleGetObject(String key)`	Gets an object for the given key from this resource bundle.
`protected Set<String>`	`handleKeySet()`	Returns a `Set` of the keys contained *only* in this `ResourceBundle`.

Methods inherited from class java.util.ResourceBundle

clearCache, clearCache, containsKey, getBaseBundleName, getBundle, getBundle, getBundle, getBundle, getBundle, getBundle, getLocale, getObject, getString, getStringArray, keySet, setParent

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

PropertyResourceBundle

```
public PropertyResourceBundle(InputStream stream)
                       throws IOException
```

Creates a property resource bundle from an InputStream. The property file read with this constructor must be encoded in ISO-8859-1.

Parameters:

`stream - an InputStream that represents a property file to read from.`

Throws:

`IOException - if an I/O error occurs`

`NullPointerException - if stream is null`

`IllegalArgumentException - if stream contains a malformed Unicode escape sequence.`

PropertyResourceBundle

```
public PropertyResourceBundle(Reader reader)
                       throws IOException
```

Creates a property resource bundle from a Reader. Unlike the constructor PropertyResourceBundle(InputStream), there is no limitation as to the encoding of the input property file.

Parameters:

`reader - a Reader that represents a property file to read from.`

Throws:

`IOException - if an I/O error occurs`

NullPointerException - if reader is null

IllegalArgumentException - if a malformed Unicode escape sequence appears from reader.

Since:

1.6

Method Detail

handleGetObject

```
public Object handleGetObject(String key)
```

Description copied from class: ResourceBundle

Gets an object for the given key from this resource bundle. Returns null if this resource bundle does not contain an object for the given key.

Specified by:

handleGetObject in class ResourceBundle

Parameters:

key - the key for the desired object

Returns:

the object for the given key, or null

getKeys

```
public Enumeration<String> getKeys()
```

Returns an Enumeration of the keys contained in this ResourceBundle and its parent bundles.

Specified by:

getKeys in class ResourceBundle

Returns:

an Enumeration of the keys contained in this ResourceBundle and its parent bundles.

See Also:

ResourceBundle.keySet()

handleKeySet

```
protected Set<String> handleKeySet()
```

Returns a Set of the keys contained *only* in this ResourceBundle.

Overrides:

handleKeySet in class ResourceBundle

Returns:

a Set of the keys contained only in this ResourceBundle

Since:

1.6

See Also:

ResourceBundle.keySet()

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.