JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class ServiceConfigurationError

java.lang.Object
    java.lang.Throwable
        java.lang.Error
            java.util.ServiceConfigurationError

All Implemented Interfaces:

Serializable

```
public class ServiceConfigurationError
extends Error
```

Error thrown when something goes wrong while loading a service provider.

This error will be thrown in the following situations:

- The format of a provider-configuration file violates the specification;
- An `IOException` occurs while reading a provider-configuration file;
- A concrete provider class named in a provider-configuration file cannot be found;
- A concrete provider class is not a subclass of the service class;
- A concrete provider class cannot be instantiated; or
- Some other kind of error occurs.

Since:

1.6

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`ServiceConfigurationError(String msg)`	Constructs a new instance with the specified message.
`ServiceConfigurationError(String msg, Throwable cause)`	Constructs a new instance with the specified message and cause.

Method Summary

Methods inherited from class java.lang.Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Detail

ServiceConfigurationError

```
public ServiceConfigurationError(String msg)
```

Constructs a new instance with the specified message.

Parameters:

`msg - The message, or null if there is no message`

ServiceConfigurationError

```
public ServiceConfigurationError(String msg,
                                 Throwable cause)
```

Constructs a new instance with the specified message and cause.

Parameters:

`msg - The message, or null if there is no message`

`cause - The cause, or null if the cause is nonexistent or unknown`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.