JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Interface Spliterator.OfPrimitive<T,T_CONS,T_SPLITR extends Spliterator.OfPrimitive<T,T_CONS,T_SPLITR>>

Type Parameters:

`T` - the type of elements returned by this Spliterator. The type must be a wrapper type for a primitive type, such as Integer for the primitive int type.

`T_CONS` - the type of primitive consumer. The type must be a primitive specialization of `Consumer` for T, such as `IntConsumer` for Integer.

`T_SPLITR` - the type of primitive Spliterator. The type must be a primitive specialization of Spliterator for T, such as `Spliterator.OfInt` for Integer.

All Superinterfaces:

`Spliterator`<T>

All Known Subinterfaces:

`Spliterator.OfDouble`, `Spliterator.OfInt`, `Spliterator.OfLong`

All Known Implementing Classes:

`Spliterators.AbstractDoubleSpliterator`, `Spliterators.AbstractIntSpliterator`, `Spliterators.AbstractLongSpliterator`

Enclosing interface:

`Spliterator`<T>

```
public static interface Spliterator.OfPrimitive<T,T_CONS,T_SPLITR extends Spliterat
extends Spliterator<T>
```

A Spliterator specialized for primitive values.

Since:

1.8

See Also:

Spliterator.OfInt, Spliterator.OfLong, Spliterator.OfDouble

Nested Class Summary

Nested classes/interfaces inherited from interface java.util.Spliterator

Spliterator.OfDouble, Spliterator.OfInt, Spliterator.OfLong, Spliterator.OfPrimitive<T,T_CONS,T_SPLITR extends Spliterator.OfPrimitive<T,T_CONS,T_SPLITR>>

Field Summary

Fields inherited from interface java.util.Spliterator

CONCURRENT, DISTINCT, IMMUTABLE, NONNULL, ORDERED, SIZED, SORTED, SUBSIZED

Method Summary

Abstract Methods | Default Methods

Modifier and Type	Method	Description
default void	**forEachRemaining**(T_CONS action)	Performs the given action for each remaining element, sequentially in the current thread, until all elements have been processed or the action throws an exception.
boolean	**tryAdvance**(T_CONS action)	If a remaining element exists, performs the

		given action on it, returning `true`; else returns `false`.
`T_SPLITR`	`trySplit()`	If this spliterator can be partitioned, returns a Spliterator covering elements, that will, upon return from this method, not be covered by this Spliterator.

Methods inherited from interface java.util.Spliterator

`characteristics`, `estimateSize`, `forEachRemaining`, `getComparator`, `getExactSizeIfKnown`, `hasCharacteristics`, `tryAdvance`

Method Detail

trySplit

`T_SPLITR trySplit()`

Description copied from interface: `Spliterator`
If this spliterator can be partitioned, returns a Spliterator covering elements, that will, upon return from this method, not be covered by this Spliterator.

If this Spliterator is `Spliterator.ORDERED`, the returned Spliterator must cover a strict prefix of the elements.

Unless this Spliterator covers an infinite number of elements, repeated calls to `trySplit()` must eventually return `null`. Upon non-null return:

- the value reported for `estimateSize()` before splitting, must, after splitting, be greater than or equal to `estimateSize()` for this and the returned Spliterator; and
- if this Spliterator is `SUBSIZED`, then `estimateSize()` for this spliterator before splitting must be equal to the sum of `estimateSize()` for this and the returned Spliterator after splitting.

This method may return `null` for any reason, including emptiness, inability to split after traversal has commenced, data structure constraints, and efficiency considerations.

Specified by:

`trySplit` in interface `Spliterator<T>`

Returns:

a Spliterator covering some portion of the elements, or null if this spliterator cannot be split

tryAdvance

```
boolean tryAdvance(T_CONS action)
```

If a remaining element exists, performs the given action on it, returning `true`; else returns `false`. If this Spliterator is `Spliterator.ORDERED` the action is performed on the next element in encounter order. Exceptions thrown by the action are relayed to the caller.

Parameters:

`action` - The action

Returns:

false if no remaining elements existed upon entry to this method, else true.

Throws:

`NullPointerException` - if the specified action is null

forEachRemaining

```
default void forEachRemaining(T_CONS action)
```

Performs the given action for each remaining element, sequentially in the current thread, until all elements have been processed or the action throws an exception. If this Spliterator is `Spliterator.ORDERED`, actions are performed in encounter order. Exceptions thrown by the action are relayed to the caller.

Implementation Requirements:

The default implementation repeatedly invokes `tryAdvance(T_CONS)` until it returns false. It should be overridden whenever possible.

Parameters:

`action` - The action

Throws:

`NullPointerException` - if the specified action is null

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.