JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.concurrent

Class ExecutionException

java.lang.Object
    java.lang.Throwable
        java.lang.Exception
            java.util.concurrent.ExecutionException

All Implemented Interfaces:

Serializable

```
public class ExecutionException
extends Exception
```

Exception thrown when attempting to retrieve the result of a task that aborted by throwing an exception. This exception can be inspected using the `Throwable.getCause()` method.

Since:

1.5

See Also:

Future, Serialized Form

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**ExecutionException**()	Constructs an ExecutionException with no detail message.

protected	**ExecutionException**(**String** message)	Constructs an ExecutionException with the specified detail message.
	ExecutionException(**String** message, **Throwable** cause)	Constructs an ExecutionException with the specified detail message and cause.
	ExecutionException(**Throwable** cause)	Constructs an ExecutionException with the specified cause.

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

ExecutionException

```
protected ExecutionException()
```

Constructs an ExecutionException with no detail message. The cause is not initialized, and may subsequently be initialized by a call to initCause.

ExecutionException

```
protected ExecutionException(String message)
```

Constructs an ExecutionException with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to initCause.

Parameters:

message - the detail message

ExecutionException

```
public ExecutionException(String message,
                          Throwable cause)
```

Constructs an ExecutionException with the specified detail message and cause.

Parameters:

message - the detail message

cause - the cause (which is saved for later retrieval by the Throwable.getCause() method)

ExecutionException

```
public ExecutionException(Throwable cause)
```

Constructs an ExecutionException with the specified cause. The detail message is set to (cause == null ? null : cause.toString()) (which typically contains the class and detail message of cause).

Parameters:

cause - the cause (which is saved for later retrieval by the Throwable.getCause() method)

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.