JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.concurrent

Class RejectedExecutionException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.util.concurrent.RejectedExecutionException

All Implemented Interfaces:

Serializable

```
public class RejectedExecutionException
extends RuntimeException
```

Exception thrown by an `Executor` when a task cannot be accepted for execution.

Since:

1.5

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`RejectedExecutionException()`	Constructs a RejectedExecutionExc with no detail message.
`RejectedExecutionException(String message)`	Constructs a RejectedExecutionExc

	with the specified detai message.
RejectedExecutionException(**String** message, **Throwable** cause)	Constructs a RejectedExecutionExc with the specified detai message and cause.
RejectedExecutionException(**Throwable** cause)	Constructs a RejectedExecutionExc with the specified cause

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

RejectedExecutionException

```
public RejectedExecutionException()
```

Constructs a RejectedExecutionException with no detail message. The cause is not initialized, and may subsequently be initialized by a call to initCause.

RejectedExecutionException

```
public RejectedExecutionException(String message)
```

Constructs a RejectedExecutionException with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to initCause.

Parameters:

message - the detail message

RejectedExecutionException

```
public RejectedExecutionException(String message,
                                  Throwable cause)
```

Constructs a `RejectedExecutionException` with the specified detail message and cause.

Parameters:

`message - the detail message`

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method)`

RejectedExecutionException

```
public RejectedExecutionException(Throwable cause)
```

Constructs a `RejectedExecutionException` with the specified cause. The detail message is set to `(cause == null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Parameters:

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method)`

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.