JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.concurrent

Interface ThreadFactory

`public interface ThreadFactory`

An object that creates new threads on demand. Using thread factories removes hardwiring of calls to `new Thread`, enabling applications to use special thread subclasses, priorities, etc.

The simplest implementation of this interface is just:

```
class SimpleThreadFactory implements ThreadFactory {
  public Thread newThread(Runnable r) {
    return new Thread(r);
  }
}
```

The `Executors.defaultThreadFactory()` method provides a more useful simple implementation, that sets the created thread context to known values before returning it.

Since:

1.5

Method Summary

Abstract Methods

Modifier and Type	Method	Description
`Thread`	`newThread(Runnable r)`	Constructs a new Thread.

Method Detail

newThread

`Thread newThread(Runnable r)`

Constructs a new `Thread`. Implementations may also initialize priority, name, daemon status, `ThreadGroup`, etc.

Parameters:

`r - a runnable to be executed by new thread instance`

Returns:

`constructed thread, or null if the request to create a thread is rejected`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.