JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.concurrent.locks

Class AbstractOwnableSynchronizer

java.lang.Object
  java.util.concurrent.locks.AbstractOwnableSynchronizer

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

AbstractQueuedLongSynchronizer, AbstractQueuedSynchronizer

```
public abstract class AbstractOwnableSynchronizer
extends Object
implements Serializable
```

A synchronizer that may be exclusively owned by a thread. This class provides a basis for creating locks and related synchronizers that may entail a notion of ownership. The `AbstractOwnableSynchronizer` class itself does not manage or use this information. However, subclasses and tools may use appropriately maintained values to help control and monitor access and provide diagnostics.

Since:

1.6

See Also:

Serialized Form

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	AbstractOwnableSynchronizer()	

		Empty constructor for use by subclasses.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
protected `Thread`	`getExclusiveOwnerThread()`	Returns the thread last set by `setExclusiveOwnerThread`, or `null` if never set.
protected void	`setExclusiveOwnerThread(Thread thread)`	Sets the thread that currently owns exclusive access.

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

AbstractOwnableSynchronizer

```
protected AbstractOwnableSynchronizer()
```

Empty constructor for use by subclasses.

Method Detail

setExclusiveOwnerThread

```
protected final void setExclusiveOwnerThread(Thread thread)
```

Sets the thread that currently owns exclusive access. A `null` argument indicates that no thread owns access. This method does not otherwise impose any synchronization or `volatile` field accesses.

Parameters:

thread - the owner thread

getExclusiveOwnerThread

```
protected final Thread getExclusiveOwnerThread()
```

Returns the thread last set by `setExclusiveOwnerThread`, or `null` if never set. This method does not otherwise impose any synchronization or `volatile` field accesses.

Returns:

the owner thread

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.