JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.function

Interface LongPredicate

Functional Interface:

This is a functional interface and can therefore be used as the assignment target for a lambda expression or method reference.

```
@FunctionalInterface
public interface LongPredicate
```

Represents a predicate (boolean-valued function) of one `long`-valued argument. This is the `long`-consuming primitive type specialization of `Predicate`.

This is a functional interface whose functional method is `test(long)`.

Since:

1.8

See Also:

`Predicate`

Method Summary

Abstract Methods | **Default Methods**

Modifier and Type	Method	Description
default `LongPredicate`	`and(LongPredicate other)`	Returns a composed predicate that represents a short-circuiting logical

		AND of this predicate and another.
default LongPredicate	negate()	Returns a predicate that represents the logical negation of this predicate.
default LongPredicate	or(LongPredicate other)	Returns a composed predicate that represents a short-circuiting logical OR of this predicate and another.
boolean	test(long value)	Evaluates this predicate on the given argument.

Method Detail

test

`boolean test(long value)`

Evaluates this predicate on the given argument.

Parameters:

`value - the input argument`

Returns:

`true if the input argument matches the predicate, otherwise false`

and

`default LongPredicate and(LongPredicate other)`

Returns a composed predicate that represents a short-circuiting logical AND of this predicate and another. When evaluating the composed predicate, if this predicate is `false`, then the `other` predicate is not evaluated.

Any exceptions thrown during evaluation of either predicate are relayed to the caller; if evaluation of this predicate throws an exception, the `other` predicate will not be evaluated.

Parameters:

`other - a predicate that will be logically-ANDed with this predicate`

Returns:

`a composed predicate that represents the short-circuiting logical AND of this predicate and the other predicate`

Throws:

`NullPointerException - if other is null`

negate

`default LongPredicate negate()`

Returns a predicate that represents the logical negation of this predicate.

Returns:

`a predicate that represents the logical negation of this predicate`

or

`default LongPredicate or(LongPredicate other)`

Returns a composed predicate that represents a short-circuiting logical OR of this predicate and another. When evaluating the composed predicate, if this predicate is `true`, then the `other` predicate is not evaluated.

Any exceptions thrown during evaluation of either predicate are relayed to the caller; if evaluation of this predicate throws an exception, the `other` predicate will not be evaluated.

Parameters:

`other - a predicate that will be logically-ORed with this predicate`

Returns:

`a composed predicate that represents the short-circuiting logical OR of this predicate and the other predicate`

Throws:

```
NullPointerException - if other is null
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.