JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.jar

Class Attributes.Name

java.lang.Object
    java.util.jar.Attributes.Name

Enclosing class:

Attributes

```
public static class Attributes.Name
extends Object
```

The Attributes.Name class represents an attribute name stored in this Map. Valid attribute names are case-insensitive, are restricted to the ASCII characters in the set [0-9a-zA-Z_-], and cannot exceed 70 characters in length. Attribute values can contain any characters and will be UTF8-encoded when written to the output stream. See the JAR File Specification for more information about valid attribute names and values.

Field Summary

Fields

Modifier and Type	Field	Description
static Attributes.Name	CLASS_PATH	Name object for Class-Path manifest attribute.
static Attributes.Name	CONTENT_TYPE	Name object for Content-Type manifest attribute.
static Attributes.Name	EXTENSION_INSTALLATION	**Deprecated.**

		Extension mechanism will be removed in a future release. Use class path instead.
static **Attributes.Name**	**EXTENSION_LIST**	Name object for `Extension-List` manifest attribute used for declaring dependencies on installed extensions.
static **Attributes.Name**	**EXTENSION_NAME**	Name object for `Extension-Name` manifest attribute used for declaring dependencies on installed extensions.
static **Attributes.Name**	**IMPLEMENTATION_TITLE**	Name object for `Implementation-Title` manifest attribute used for package versioning.
static **Attributes.Name**	**IMPLEMENTATION_URL**	**Deprecated.** Extension mechanism will be removed in a future release. Use class path instead.
static **Attributes.Name**	**IMPLEMENTATION_VENDOR**	Name object for `Implementation-Vendor` manifest attribute used for package versioning.
static **Attributes.Name**	**IMPLEMENTATION_VENDOR_ID**	**Deprecated.** Extension mechanism will be removed in a

		future release. Use class path instead.
static **Attributes.Name**	**IMPLEMENTATION_VERSION**	Name object for `Implementation-Version` manifest attribute used for package versioning.
static **Attributes.Name**	**MAIN_CLASS**	Name object for `Main-Class` manifest attribute used for launching applications packaged in JAR files.
static **Attributes.Name**	**MANIFEST_VERSION**	Name object for `Manifest-Version` manifest attribute.
static **Attributes.Name**	**SEALED**	Name object for `Sealed` manifest attribute used for sealing.
static **Attributes.Name**	**SIGNATURE_VERSION**	Name object for `Signature-Version` manifest attribute used when signing JAR files.
static **Attributes.Name**	**SPECIFICATION_TITLE**	Name object for `Specification-Title` manifest attribute used for package versioning.
static **Attributes.Name**	**SPECIFICATION_VENDOR**	Name object for `Specification-Vendor` manifest attribute used for package versioning.

static Attributes.Name	SPECIFICATION_VERSION	Name object for Specification-Version manifest attribute used for package versioning.

Constructor Summary

Constructors

Constructor	Description
Name(String name)	Constructs a new attribute name using the given string name.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
boolean	equals(Object o)	Compares this attribute name to another for equality.
int	hashCode()	Computes the hash value for this attribute name.
String	toString()	Returns the attribute name as a String.

Methods inherited from class java.lang.Object

clone, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

MANIFEST_VERSION

```
public static final Attributes.Name MANIFEST_VERSION
```

Name object for `Manifest-Version` manifest attribute. This attribute indicates the version number of the manifest standard to which a JAR file's manifest conforms.

See Also:

Manifest and Signature Specification

SIGNATURE_VERSION

```
public static final Attributes.Name SIGNATURE_VERSION
```

Name object for `Signature-Version` manifest attribute used when signing JAR files.

See Also:

Manifest and Signature Specification

CONTENT_TYPE

```
public static final Attributes.Name CONTENT_TYPE
```

Name object for `Content-Type` manifest attribute.

CLASS_PATH

```
public static final Attributes.Name CLASS_PATH
```

Name object for `Class-Path` manifest attribute. Bundled extensions can use this attribute to find other JAR files containing needed classes.

See Also:

JAR file specification

MAIN_CLASS

```
public static final Attributes.Name MAIN_CLASS
```

Name object for `Main-Class` manifest attribute used for launching applications packaged in JAR files. The `Main-Class` attribute is used in conjunction with the `-jar` command-line option of the `java` application launcher.

SEALED

```
public static final Attributes.Name SEALED
```

Name object for `Sealed` manifest attribute used for sealing.

See Also:

Package Sealing

EXTENSION_LIST

```
public static final Attributes.Name EXTENSION_LIST
```

Name object for `Extension-List` manifest attribute used for declaring dependencies on installed extensions.

See Also:

Installed extension dependency

EXTENSION_NAME

```
public static final Attributes.Name EXTENSION_NAME
```

Name object for `Extension-Name` manifest attribute used for declaring dependencies on installed extensions.

See Also:

Installed extension dependency

EXTENSION_INSTALLATION

```
@Deprecated
public static final Attributes.Name EXTENSION_INSTALLATION
```

Deprecated. *Extension mechanism will be removed in a future release. Use class path instead.*

Name object for `Extension-Name` manifest attribute used for declaring dependencies on installed extensions.

See Also:

Installed extension dependency

IMPLEMENTATION_TITLE

```
public static final Attributes.Name IMPLEMENTATION_TITLE
```

Name object for `Implementation-Title` manifest attribute used for package versioning.

See Also:

Java Product Versioning Specification

IMPLEMENTATION_VERSION

```
public static final Attributes.Name IMPLEMENTATION_VERSION
```

Name object for `Implementation-Version` manifest attribute used for package versioning.

See Also:

Java Product Versioning Specification

IMPLEMENTATION_VENDOR

```
public static final Attributes.Name IMPLEMENTATION_VENDOR
```

Name object for `Implementation-Vendor` manifest attribute used for package versioning.

See Also:

Java Product Versioning Specification

IMPLEMENTATION_VENDOR_ID

```
@Deprecated
public static final Attributes.Name IMPLEMENTATION_VENDOR_ID
```

Deprecated. *Extension mechanism will be removed in a future release. Use class path instead.*

Name object for `Implementation-Vendor-Id` manifest attribute used for package versioning.

See Also:

Optional Package Versioning

IMPLEMENTATION_URL

```
@Deprecated
public static final Attributes.Name IMPLEMENTATION_URL
```

Deprecated. *Extension mechanism will be removed in a future release. Use class path instead.*

Name object for `Implementation-URL` manifest attribute used for package versioning.

See Also:

Optional Package Versioning

SPECIFICATION_TITLE

```
public static final Attributes.Name SPECIFICATION_TITLE
```

Name object for `Specification-Title` manifest attribute used for package versioning.

See Also:

Java Product Versioning Specification

SPECIFICATION_VERSION

```
public static final Attributes.Name SPECIFICATION_VERSION
```

Name object for `Specification-Version` manifest attribute used for package versioning.

See Also:

Java Product Versioning Specification

SPECIFICATION_VENDOR

```
public static final Attributes.Name SPECIFICATION_VENDOR
```

Name object for `Specification-Vendor` manifest attribute used for package versioning.

See Also:

Java Product Versioning Specification

Constructor Detail

Name

```
public Name(String name)
```

Constructs a new attribute name using the given string name.

Parameters:

`name` - the attribute string name

Throws:

`IllegalArgumentException` - if the attribute name was invalid

`NullPointerException` - if the attribute name was null

Method Detail

equals

```
public boolean equals(Object o)
```

Compares this attribute name to another for equality.

Overrides:

`equals` in class `Object`

Parameters:

`o` - the object to compare

Returns:

true if this attribute name is equal to the specified attribute object

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

Computes the hash value for this attribute name.

Overrides:

`hashCode` in class `Object`

Returns:

a hash code value for this object.

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

toString

```
public String toString()
```

Returns the attribute name as a String.

Overrides:

`toString` in class `Object`

Returns:

a string representation of the object.

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.