JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.jar

Class Attributes

java.lang.Object
    java.util.jar.Attributes

All Implemented Interfaces:

`Cloneable, Map<Object,Object>`

```
public class Attributes
extends Object
implements Map<Object,Object>, Cloneable
```

The Attributes class maps Manifest attribute names to associated string values. Valid attribute names are case-insensitive, are restricted to the ASCII characters in the set [0-9a-zA-Z_-], and cannot exceed 70 characters in length. Attribute values can contain any characters and will be UTF8-encoded when written to the output stream. See the JAR File Specification for more information about valid attribute names and values.

Since:

1.2

See Also:

`Manifest`

Nested Class Summary

Nested Classes

Modifier and Type	Class	Description

static class	Attributes.Name	The Attributes.Name class represents an attribute name stored in this Map.

Nested classes/interfaces inherited from interface java.util.Map

Map.Entry<K,V>

Field Summary

Fields

Modifier and Type	Field	Description
protected Map<Object,Object>	map	The attribute name-value mappings.

Constructor Summary

Constructors

Constructor	Description
Attributes()	Constructs a new, empty Attributes object with default size.
Attributes(Attributes attr)	Constructs a new Attributes object with the same attribute name-value mappings as in the specified Attributes.
Attributes(int size)	Constructs a new, empty Attributes object with the specified initial size.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
void	clear()	Removes all attributes from this Map.

Object	**clone**()	Returns a copy of the Attributes, implemented as follows:
boolean	**containsKey**(**Object** name)	Returns true if this Map contains the specified attribute name (key).
boolean	**containsValue**(**Object** value)	Returns true if this Map maps one or more attribute names (keys) to the specified value.
Set<**Map.Entry**<**Object**,**Object**>>	**entrySet**()	Returns a Collection view of the attribute name-value mappings contained in this Map.
boolean	**equals**(**Object** o)	Compares the specified Attributes object with this Map for equality.
Object	**get**(**Object** name)	Returns the value of the specified attribute name, or null if the attribute name was not found.
String	**getValue**(**Attributes.Name** name)	Returns the value of the specified Attributes.Name, or null if the attribute was not found.

String	**getValue**(**String** name)	Returns the value of the specified attribute name, specified as a string, or null if the attribute was not found.
int	**hashCode**()	Returns the hash code value for this Map.
boolean	**isEmpty**()	Returns true if this Map contains no attributes.
Set<**Object**>	**keySet**()	Returns a Set view of the attribute names (keys) contained in this Map.
Object	**put**(**Object** name, **Object** value)	Associates the specified value with the specified attribute name (key) in this Map.
void	**putAll**(**Map**<?,?> attr)	Copies all of the attribute name-value mappings from the specified Attributes to this Map.
String	**putValue**(**String** name, **String** value)	Associates the specified value with the specified attribute name, specified as a String.
Object	**remove**(**Object** name)	

		Removes the attribute with the specified name (key) from this Map.
int	**size**()	Returns the number of attributes in this Map.
Collection<**Object**>	**values**()	Returns a Collection view of the attribute values contained in this Map.

Methods inherited from class java.lang.Object

finalize, getClass, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.util.Map

compute, computeIfAbsent, computeIfPresent, forEach, getOrDefault, merge, putIfAbsent, remove, replace, replace, replaceAll

Field Detail

map

```
protected Map<Object,Object> map
```

The attribute name-value mappings.

Constructor Detail

Attributes

```
public Attributes()
```

Constructs a new, empty Attributes object with default size.

Attributes

```
public Attributes(int size)
```

Constructs a new, empty Attributes object with the specified initial size.

Parameters:

`size - the initial number of attributes`

Attributes

```
public Attributes(Attributes attr)
```

Constructs a new Attributes object with the same attribute name-value mappings as in the specified Attributes.

Parameters:

`attr - the specified Attributes`

Method Detail

get

```
public Object get(Object name)
```

Returns the value of the specified attribute name, or null if the attribute name was not found.

Specified by:

`get in interface Map<Object,Object>`

Parameters:

`name - the attribute name`

Returns:

`the value of the specified attribute name, or null if not found.`

getValue

```
public String getValue(String name)
```

Returns the value of the specified attribute name, specified as a string, or null if the attribute was not found. The attribute name is case-insensitive.

This method is defined as:

```
return (String)get(new Attributes.Name((String)name));
```

Parameters:

name - the attribute name as a string

Returns:

the String value of the specified attribute name, or null if not found.

Throws:

IllegalArgumentException - if the attribute name is invalid

getValue

```
public String getValue(Attributes.Name name)
```

Returns the value of the specified Attributes.Name, or null if the attribute was not found.

This method is defined as:

```
return (String)get(name);
```

Parameters:

name - the Attributes.Name object

Returns:

the String value of the specified Attribute.Name, or null if not found.

put

```
public Object put(Object name,
                  Object value)
```

Associates the specified value with the specified attribute name (key) in this Map. If the Map previously contained a mapping for the attribute name, the old value is replaced.

Specified by:

put in interface Map<Object,Object>

Parameters:

name - the attribute name

value - the attribute value

Returns:

the previous value of the attribute, or null if none

Throws:

ClassCastException - if the name is not a Attributes.Name or the value is not a String

putValue

```
public String putValue(String name,
                       String value)
```

Associates the specified value with the specified attribute name, specified as a String. The attributes name is case-insensitive. If the Map previously contained a mapping for the attribute name, the old value is replaced.

This method is defined as:

```
return (String)put(new Attributes.Name(name), value);
```

Parameters:

name - the attribute name as a string

value - the attribute value

Returns:

the previous value of the attribute, or null if none

Throws:

IllegalArgumentException - if the attribute name is invalid

remove

```
public Object remove(Object name)
```

Removes the attribute with the specified name (key) from this Map. Returns the previous attribute value, or null if none.

Specified by:

remove in interface Map<Object,Object>

Parameters:

name - attribute name

Returns:

the previous value of the attribute, or null if none

containsValue

```
public boolean containsValue(Object value)
```

Returns true if this Map maps one or more attribute names (keys) to the specified value.

Specified by:

`containsValue` in interface `Map<Object,Object>`

Parameters:

`value` - the attribute value

Returns:

`true if this Map maps one or more attribute names to the specified value`

containsKey

```
public boolean containsKey(Object name)
```

Returns true if this Map contains the specified attribute name (key).

Specified by:

`containsKey` in interface `Map<Object,Object>`

Parameters:

`name` - the attribute name

Returns:

`true if this Map contains the specified attribute name`

putAll

```
public void putAll(Map<?,?> attr)
```

Copies all of the attribute name-value mappings from the specified Attributes to this Map. Duplicate mappings will be replaced.

Specified by:

`putAll` in interface `Map<Object,Object>`

Parameters:

`attr` - the Attributes to be stored in this map

Throws:

`ClassCastException` - if attr is not an Attributes

clear

```
public void clear()
```

Removes all attributes from this Map.

Specified by:

`clear` in interface `Map<Object,Object>`

size

```
public int size()
```

Returns the number of attributes in this Map.

Specified by:

`size` in interface `Map<Object,Object>`

Returns:

the number of key-value mappings in this map

isEmpty

```
public boolean isEmpty()
```

Returns true if this Map contains no attributes.

Specified by:

`isEmpty` in interface `Map<Object,Object>`

Returns:

true if this map contains no key-value mappings

keySet

```
public Set<Object> keySet()
```

Returns a Set view of the attribute names (keys) contained in this Map.

Specified by:

`keySet` in interface `Map<Object,Object>`

Returns:

a set view of the keys contained in this map

values

```
public Collection<Object> values()
```

Returns a Collection view of the attribute values contained in this Map.

Specified by:

`values` in interface `Map<Object,Object>`

Returns:

a collection view of the values contained in this map

entrySet

```
public Set<Map.Entry<Object,Object>> entrySet()
```

Returns a Collection view of the attribute name-value mappings contained in this Map.

Specified by:

`entrySet` in interface `Map<Object,Object>`

Returns:

a set view of the mappings contained in this map

equals

```
public boolean equals(Object o)
```

Compares the specified Attributes object with this Map for equality. Returns true if the given object is also an instance of Attributes and the two Attributes objects represent the same mappings.

Specified by:

`equals` in interface `Map<Object,Object>`

Overrides:

`equals` in class `Object`

Parameters:

o - the Object to be compared

Returns:

true if the specified Object is equal to this Map

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

Returns the hash code value for this Map.

Specified by:

`hashCode` in interface `Map<Object,Object>`

Overrides:

`hashCode` in class `Object`

Returns:

a hash code value for this object.

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

clone

```
public Object clone()
```

Returns a copy of the Attributes, implemented as follows:

```
public Object clone() { return new Attributes(this); }
```

Since the attribute names and values are themselves immutable, the Attributes returned can be safely modified without affecting the original.

Overrides:

`clone` in class `Object`

Returns:

a clone of this instance.

See Also:

```
Cloneable
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.