JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.jar

Class JarEntry

java.lang.Object
    java.util.zip.ZipEntry
        java.util.jar.JarEntry

All Implemented Interfaces:

`Cloneable`

```
public class JarEntry
extends ZipEntry
```

This class is used to represent a JAR file entry.

Field Summary

Fields

Modifier and Type	Field	Description
static int	**CENATT**	
static int	**CENATX**	
static int	**CENCOM**	
static int	**CENCRC**	
static int	**CENDSK**	
static int	**CENEXT**	
static int	**CENFLG**	
static int	**CENHDR**	

static int	**CENHOW**	
static int	**CENLEN**	
static int	**CENNAM**	
static int	**CENOFF**	
static long	**CENSIG**	
static int	**CENSIZ**	
static int	**CENTIM**	
static int	**CENVEM**	
static int	**CENVER**	
static int	**ENDCOM**	
static int	**ENDHDR**	
static int	**ENDOFF**	
static long	**ENDSIG**	
static int	**ENDSIZ**	
static int	**ENDSUB**	
static int	**ENDTOT**	
static int	**EXTCRC**	
static int	**EXTHDR**	
static int	**EXTLEN**	
static long	**EXTSIG**	
static int	**EXTSIZ**	
static int	**LOCCRC**	
static int	**LOCEXT**	
static int	**LOCFLG**	
static int	**LOCHDR**	
static int	**LOCHOW**	
static int	**LOCLEN**	
static int	**LOCNAM**	
static long	**LOCSIG**	

static int	LOCSIZ	
static int	LOCTIM	
static int	LOCVER	

Fields inherited from class java.util.zip.ZipEntry

DEFLATED, STORED

Constructor Summary

Constructors

Constructor	Description
JarEntry(JarEntry je)	Creates a new JarEntry with fields taken from the specified JarEntry object.
JarEntry(String name)	Creates a new JarEntry for the specified JAR file entry name.
JarEntry(ZipEntry ze)	Creates a new JarEntry with fields taken from the specified ZipEntry object.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
Attributes	getAttributes()	Returns the Manifest Attributes for this entry, or null if none.
Certificate[]	getCertificates()	Returns the Certificate objects for this entry, or null if none.
CodeSigner[]	getCodeSigners()	Returns the CodeSigner objects for this entry, or null if none.

Methods inherited from class java.util.zip.ZipEntry

clone, getComment, getCompressedSize, getCrc, getCreationTime, getExtra, getLastAccessTime, getLastModifiedTime, getMethod, getName, getSize, getTime, hashCode, isDirectory, setComment, setCompressedSize, setCrc, setCreationTime, setExtra,

setLastAccessTime, setLastModifiedTime, setMethod, setSize, setTime, toString

Methods inherited from class java.lang.Object

equals, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

LOCSIG

public static final long LOCSIG

See Also:

Constant Field Values

EXTSIG

public static final long EXTSIG

See Also:

Constant Field Values

CENSIG

public static final long CENSIG

See Also:

Constant Field Values

ENDSIG

public static final long ENDSIG

See Also:

Constant Field Values

LOCHDR

public static final int LOCHDR

See Also:

Constant Field Values

EXTHDR

```
public static final int EXTHDR
```

See Also:

Constant Field Values

CENHDR

```
public static final int CENHDR
```

See Also:

Constant Field Values

ENDHDR

```
public static final int ENDHDR
```

See Also:

Constant Field Values

LOCVER

```
public static final int LOCVER
```

See Also:

Constant Field Values

LOCFLG

```
public static final int LOCFLG
```

See Also:

Constant Field Values

LOCHOW

public static final int LOCHOW

See Also:

Constant Field Values

LOCTIM

public static final int LOCTIM

See Also:

Constant Field Values

LOCCRC

public static final int LOCCRC

See Also:

Constant Field Values

LOCSIZ

public static final int LOCSIZ

See Also:

Constant Field Values

LOCLEN

public static final int LOCLEN

See Also:

Constant Field Values

LOCNAM

public static final int LOCNAM

See Also:

Constant Field Values

LOCEXT

public static final int LOCEXT

See Also:

Constant Field Values

EXTCRC

public static final int EXTCRC

See Also:

Constant Field Values

EXTSIZ

public static final int EXTSIZ

See Also:

Constant Field Values

EXTLEN

public static final int EXTLEN

See Also:

Constant Field Values

CENVEM

public static final int CENVEM

See Also:

Constant Field Values

CENVER

public static final int CENVER

See Also:

Constant Field Values

CENFLG

public static final int CENFLG

See Also:

Constant Field Values

CENHOW

public static final int CENHOW

See Also:

Constant Field Values

CENTIM

public static final int CENTIM

See Also:

Constant Field Values

CENCRC

public static final int CENCRC

See Also:

Constant Field Values

CENSIZ

public static final int CENSIZ

See Also:

Constant Field Values

CENLEN

public static final int CENLEN

See Also:

Constant Field Values

CENNAM

```
public static final int CENNAM
```

See Also:

Constant Field Values

CENEXT

```
public static final int CENEXT
```

See Also:

Constant Field Values

CENCOM

```
public static final int CENCOM
```

See Also:

Constant Field Values

CENDSK

```
public static final int CENDSK
```

See Also:

Constant Field Values

CENATT

```
public static final int CENATT
```

See Also:

Constant Field Values

CENATX

```
public static final int CENATX
```

See Also:

Constant Field Values

CENOFF

```
public static final int CENOFF
```

See Also:

Constant Field Values

ENDSUB

```
public static final int ENDSUB
```

See Also:

Constant Field Values

ENDTOT

```
public static final int ENDTOT
```

See Also:

Constant Field Values

ENDSIZ

```
public static final int ENDSIZ
```

See Also:

Constant Field Values

ENDOFF

```
public static final int ENDOFF
```

See Also:

Constant Field Values

ENDCOM

```
public static final int ENDCOM
```

See Also:

Constant Field Values

Constructor Detail

JarEntry

```
public JarEntry(String name)
```

Creates a new JarEntry for the specified JAR file entry name.

Parameters:

name - the JAR file entry name

Throws:

NullPointerException - if the entry name is null

IllegalArgumentException - if the entry name is longer than 0xFFFF bytes.

JarEntry

```
public JarEntry(ZipEntry ze)
```

Creates a new JarEntry with fields taken from the specified ZipEntry object.

Parameters:

ze - the ZipEntry object to create the JarEntry from

JarEntry

```
public JarEntry(JarEntry je)
```

Creates a new JarEntry with fields taken from the specified JarEntry object.

Parameters:

je - the JarEntry to copy

Method Detail

getAttributes

```
public Attributes getAttributes()
                          throws IOException
```

Returns the `Manifest Attributes` for this entry, or `null` if none.

Returns:

`the Manifest Attributes for this entry, or null if none`

Throws:

`IOException - if an I/O error has occurred`

getCertificates

```
public Certificate[] getCertificates()
```

Returns the `Certificate` objects for this entry, or `null` if none. This method can only be called once the `JarEntry` has been completely verified by reading from the entry input stream until the end of the stream has been reached. Otherwise, this method will return `null`.

The returned certificate array comprises all the signer certificates that were used to verify this entry. Each signer certificate is followed by its supporting certificate chain (which may be empty). Each signer certificate and its supporting certificate chain are ordered bottom-to-top (i.e., with the signer certificate first and the (root) certificate authority last).

Returns:

`the Certificate objects for this entry, or null if none.`

getCodeSigners

```
public CodeSigner[] getCodeSigners()
```

Returns the `CodeSigner` objects for this entry, or `null` if none. This method can only be called once the `JarEntry` has been completely verified by reading from the entry input stream until the end of the stream has been reached. Otherwise, this method will return `null`.

The returned array comprises all the code signers that have signed this entry.

Returns:

`the CodeSigner objects for this entry, or null if none.`

Since:

1.5

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.