JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.jar

Class JarFile

java.lang.Object
    java.util.zip.ZipFile
        java.util.jar.JarFile

All Implemented Interfaces:

`Closeable`, `AutoCloseable`

```
public class JarFile
extends ZipFile
```

The `JarFile` class is used to read the contents of a jar file from any file that can be opened with `java.io.RandomAccessFile`. It extends the class `java.util.zip.ZipFile` with support for reading an optional `Manifest` entry. The `Manifest` can be used to specify meta-information about the jar file and its entries.

Unless otherwise noted, passing a `null` argument to a constructor or method in this class will cause a `NullPointerException` to be thrown. If the verify flag is on when opening a signed jar file, the content of the file is verified against its signature embedded inside the file. Please note that the verification process does not include validating the signer's certificate. A caller should inspect the return value of `JarEntry.getCodeSigners()` to further determine if the signature can be trusted.

Since:

1.2

See Also:

`Manifest`, `ZipFile`, `JarEntry`

Field Summary

Fields

Modifier and Type	Field	Description
static int	CENATT	
static int	CENATX	
static int	CENCOM	
static int	CENCRC	
static int	CENDSK	
static int	CENEXT	
static int	CENFLG	
static int	CENHDR	
static int	CENHOW	
static int	CENLEN	
static int	CENNAM	
static int	CENOFF	
static long	CENSIG	
static int	CENSIZ	
static int	CENTIM	
static int	CENVEM	
static int	CENVER	
static int	ENDCOM	
static int	ENDHDR	
static int	ENDOFF	
static long	ENDSIG	
static int	ENDSIZ	
static int	ENDSUB	
static int	ENDTOT	
static int	EXTCRC	
static int	EXTHDR	

static int	EXTLEN	
static long	EXTSIG	
static int	EXTSIZ	
static int	LOCCRC	
static int	LOCEXT	
static int	LOCFLG	
static int	LOCHDR	
static int	LOCHOW	
static int	LOCLEN	
static int	LOCNAM	
static long	LOCSIG	
static int	LOCSIZ	
static int	LOCTIM	
static int	LOCVER	
static String	MANIFEST_NAME	The JAR manifest file name.

Fields inherited from class java.util.zip.ZipFile

OPEN_DELETE, OPEN_READ

Constructor Summary

Constructors

Constructor	Description
JarFile(File file)	Creates a new JarFile to read from the specified File object.
JarFile(File file, boolean verify)	Creates a new JarFile to read from the specified File object.
JarFile(File file, boolean verify, int mode)	

	Creates a new `JarFile` to read from the specified `File` object in the specified mode.
`JarFile`(**`String`** name)	Creates a new `JarFile` to read from the specified file `name`.
`JarFile`(**`String`** name, boolean verify)	Creates a new `JarFile` to read from the specified file `name`.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`Enumeration`<**`JarEntry`**>	**`entries`**()	Returns an enumeration of the zip file entries.
`ZipEntry`	**`getEntry`**(**`String`** name)	Returns the `ZipEntry` for the given entry name or `null` if not found.
`InputStream`	**`getInputStream`**(**`ZipEntry`** ze)	Returns an input stream for reading the contents of the specified zip file entry.
`JarEntry`	**`getJarEntry`**(**`String`** name)	Returns the `JarEntry` for the given entry name or `null` if not found.
`Manifest`	**`getManifest`**()	Returns the jar file manifest, or `null` if none.

Stream<JarEntry>	stream()	Return an ordered Stream over the ZIP file entries.

Methods inherited from class java.util.zip.ZipFile

close, finalize, getComment, getName, size

Methods inherited from class java.lang.Object

clone, equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

MANIFEST_NAME

```
public static final String MANIFEST_NAME
```

The JAR manifest file name.

See Also:

Constant Field Values

LOCSIG

```
public static final long LOCSIG
```

See Also:

Constant Field Values

EXTSIG

```
public static final long EXTSIG
```

See Also:

Constant Field Values

CENSIG

```
public static final long CENSIG
```

See Also:

Constant Field Values

ENDSIG

```
public static final long ENDSIG
```

See Also:

Constant Field Values

LOCHDR

```
public static final int LOCHDR
```

See Also:

Constant Field Values

EXTHDR

```
public static final int EXTHDR
```

See Also:

Constant Field Values

CENHDR

```
public static final int CENHDR
```

See Also:

Constant Field Values

ENDHDR

```
public static final int ENDHDR
```

See Also:

Constant Field Values

LOCVER

public static final int LOCVER

See Also:

Constant Field Values

LOCFLG

public static final int LOCFLG

See Also:

Constant Field Values

LOCHOW

public static final int LOCHOW

See Also:

Constant Field Values

LOCTIM

public static final int LOCTIM

See Also:

Constant Field Values

LOCCRC

public static final int LOCCRC

See Also:

Constant Field Values

LOCSIZ

public static final int LOCSIZ

See Also:

Constant Field Values

LOCLEN

public static final int LOCLEN

See Also:

Constant Field Values

LOCNAM

public static final int LOCNAM

See Also:

Constant Field Values

LOCEXT

public static final int LOCEXT

See Also:

Constant Field Values

EXTCRC

public static final int EXTCRC

See Also:

Constant Field Values

EXTSIZ

public static final int EXTSIZ

See Also:

Constant Field Values

EXTLEN

public static final int EXTLEN

See Also:

Constant Field Values

CENVEM

public static final int CENVEM

See Also:

Constant Field Values

CENVER

public static final int CENVER

See Also:

Constant Field Values

CENFLG

public static final int CENFLG

See Also:

Constant Field Values

CENHOW

public static final int CENHOW

See Also:

Constant Field Values

CENTIM

public static final int CENTIM

See Also:

Constant Field Values

CENCRC

public static final int CENCRC

See Also:

Constant Field Values

CENSIZ

public static final int CENSIZ

See Also:

Constant Field Values

CENLEN

public static final int CENLEN

See Also:

Constant Field Values

CENNAM

public static final int CENNAM

See Also:

Constant Field Values

CENEXT

public static final int CENEXT

See Also:

Constant Field Values

CENCOM

public static final int CENCOM

See Also:

Constant Field Values

CENDSK

public static final int CENDSK

See Also:

Constant Field Values

CENATT

public static final int CENATT

See Also:

Constant Field Values

CENATX

public static final int CENATX

See Also:

Constant Field Values

CENOFF

public static final int CENOFF

See Also:

Constant Field Values

ENDSUB

public static final int ENDSUB

See Also:

Constant Field Values

ENDTOT

public static final int ENDTOT

See Also:

Constant Field Values

ENDSIZ

public static final int ENDSIZ

See Also:

Constant Field Values

ENDOFF

```
public static final int ENDOFF
```

See Also:

Constant Field Values

ENDCOM

```
public static final int ENDCOM
```

See Also:

Constant Field Values

Constructor Detail

JarFile

```
public JarFile(String name)
        throws IOException
```

Creates a new `JarFile` to read from the specified file `name`. The `JarFile` will be verified if it is signed.

Parameters:

`name` - the name of the jar file to be opened for reading

Throws:

`IOException` - if an I/O error has occurred

`SecurityException` - if access to the file is denied by the SecurityManager

JarFile

```
public JarFile(String name,
               boolean verify)
        throws IOException
```

Creates a new `JarFile` to read from the specified file `name`.

Parameters:

`name` - the name of the jar file to be opened for reading

`verify` - whether or not to verify the jar file if it is signed.

Throws:

IOException - if an I/O error has occurred

SecurityException - if access to the file is denied by the SecurityManager

JarFile

```
public JarFile(File file)
        throws IOException
```

Creates a new JarFile to read from the specified File object. The JarFile will be verified if it is signed.

Parameters:

file - the jar file to be opened for reading

Throws:

IOException - if an I/O error has occurred

SecurityException - if access to the file is denied by the SecurityManager

JarFile

```
public JarFile(File file,
               boolean verify)
        throws IOException
```

Creates a new JarFile to read from the specified File object.

Parameters:

file - the jar file to be opened for reading

verify - whether or not to verify the jar file if it is signed.

Throws:

IOException - if an I/O error has occurred

SecurityException - if access to the file is denied by the SecurityManager.

JarFile

```
public JarFile(File file,
               boolean verify,
               int mode)
        throws IOException
```

Creates a new JarFile to read from the specified File object in the specified mode. The mode argument must be either OPEN_READ or OPEN_READ | OPEN_DELETE.

Parameters:

file - the jar file to be opened for reading

verify - whether or not to verify the jar file if it is signed.

mode - the mode in which the file is to be opened

Throws:

IOException - if an I/O error has occurred

IllegalArgumentException - if the mode argument is invalid

SecurityException - if access to the file is denied by the SecurityManager

Since:

1.3

Method Detail

getManifest

```
public Manifest getManifest()
                     throws IOException
```

Returns the jar file manifest, or null if none.

Returns:

the jar file manifest, or null if none

Throws:

IllegalStateException - may be thrown if the jar file has been closed

IOException - if an I/O error has occurred

getJarEntry

```
public JarEntry getJarEntry(String name)
```

Returns the JarEntry for the given entry name or null if not found.

Parameters:

name - the jar file entry name

Returns:

the JarEntry for the given entry name or null if not found.

Throws:

IllegalStateException - may be thrown if the jar file has been closed

See Also:

JarEntry

getEntry

```
public ZipEntry getEntry(String name)
```

Returns the ZipEntry for the given entry name or null if not found.

Overrides:

getEntry in class ZipFile

Parameters:

name - the jar file entry name

Returns:

the ZipEntry for the given entry name or null if not found

Throws:

IllegalStateException - may be thrown if the jar file has been closed

See Also:

ZipEntry

entries

```
public Enumeration<JarEntry> entries()
```

Returns an enumeration of the zip file entries.

Overrides:

entries in class ZipFile

Returns:

an enumeration of the ZIP file entries

stream

```
public Stream<JarEntry> stream()
```

Description copied from class: ZipFile

Return an ordered `Stream` over the ZIP file entries. Entries appear in the `Stream` in the order they appear in the central directory of the ZIP file.

Overrides:

`stream` in class `ZipFile`

Returns:

an ordered Stream of entries in this ZIP file

getInputStream

```
public InputStream getInputStream(ZipEntry ze)
                           throws IOException
```

Returns an input stream for reading the contents of the specified zip file entry.

Overrides:

`getInputStream` in class `ZipFile`

Parameters:

ze - the zip file entry

Returns:

an input stream for reading the contents of the specified zip file entry

Throws:

`ZipException` - if a zip file format error has occurred

`IOException` - if an I/O error has occurred

`SecurityException` - if any of the jar file entries are incorrectly signed.

`IllegalStateException` - may be thrown if the jar file has been closed

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.