JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.jar

Class JarInputStream

java.lang.Object
  java.io.InputStream
    java.io.FilterInputStream
      java.util.zip.InflaterInputStream
        java.util.zip.ZipInputStream
          java.util.jar.JarInputStream

All Implemented Interfaces:

`Closeable`, `AutoCloseable`

```
public class JarInputStream
extends ZipInputStream
```

The `JarInputStream` class is used to read the contents of a JAR file from any input stream. It extends the class `java.util.zip.ZipInputStream` with support for reading an optional `Manifest` entry. The `Manifest` can be used to store meta-information about the JAR file and its entries.

Since:

`1.2`

See Also:

`Manifest`, `ZipInputStream`

Field Summary

Fields

Modifier and Type	Field	Description
`static int`	**`CENATT`**	

static int	**CENATX**	
static int	**CENCOM**	
static int	**CENCRC**	
static int	**CENDSK**	
static int	**CENEXT**	
static int	**CENFLG**	
static int	**CENHDR**	
static int	**CENHOW**	
static int	**CENLEN**	
static int	**CENNAM**	
static int	**CENOFF**	
static long	**CENSIG**	
static int	**CENSIZ**	
static int	**CENTIM**	
static int	**CENVEM**	
static int	**CENVER**	
static int	**ENDCOM**	
static int	**ENDHDR**	
static int	**ENDOFF**	
static long	**ENDSIG**	
static int	**ENDSIZ**	
static int	**ENDSUB**	
static int	**ENDTOT**	
static int	**EXTCRC**	
static int	**EXTHDR**	
static int	**EXTLEN**	
static long	**EXTSIG**	
static int	**EXTSIZ**	
static int	**LOCCRC**	

static int	LOCEXT
static int	LOCFLG
static int	LOCHDR
static int	LOCHOW
static int	LOCLEN
static int	LOCNAM
static long	LOCSIG
static int	LOCSIZ
static int	LOCTIM
static int	LOCVER

Fields inherited from class java.util.zip.InflaterInputStream

buf, inf, len

Fields inherited from class java.io.FilterInputStream

in

Constructor Summary

Constructors

Constructor	Description
JarInputStream(InputStream in)	Creates a new JarInputStream and reads the optional manifest.
JarInputStream(InputStream in, boolean verify)	Creates a new JarInputStream and reads the optional manifest.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
protected ZipEntry	createZipEntry(String name)	Creates a new JarEntry (ZipEntry) for the specified JAR file entry name.
Manifest	getManifest()	Returns the Manifest for this JAR file, or null if none.
ZipEntry	getNextEntry()	Reads the next ZIP file entry and positions the stream at the beginning of the entry data.
JarEntry	getNextJarEntry()	Reads the next JAR file entry and positions the stream at the beginning of the entry data.
int	read(byte[] b, int off, int len)	Reads from the current JAR file entry into an array of bytes.

Methods inherited from class java.util.zip.ZipInputStream

available, close, closeEntry, skip

Methods inherited from class java.util.zip.InflaterInputStream

fill, mark, markSupported, read, reset

Methods inherited from class java.io.FilterInputStream

read

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

LOCSIG

public static final long LOCSIG

See Also:

Constant Field Values

EXTSIG

public static final long EXTSIG

See Also:

Constant Field Values

CENSIG

public static final long CENSIG

See Also:

Constant Field Values

ENDSIG

public static final long ENDSIG

See Also:

Constant Field Values

LOCHDR

```
public static final int LOCHDR
```

See Also:

Constant Field Values

EXTHDR

```
public static final int EXTHDR
```

See Also:

Constant Field Values

CENHDR

```
public static final int CENHDR
```

See Also:

Constant Field Values

ENDHDR

```
public static final int ENDHDR
```

See Also:

Constant Field Values

LOCVER

```
public static final int LOCVER
```

See Also:

Constant Field Values

LOCFLG

```
public static final int LOCFLG
```

See Also:

Constant Field Values

LOCHOW

public static final int LOCHOW

See Also:

Constant Field Values

LOCTIM

public static final int LOCTIM

See Also:

Constant Field Values

LOCCRC

public static final int LOCCRC

See Also:

Constant Field Values

LOCSIZ

public static final int LOCSIZ

See Also:

Constant Field Values

LOCLEN

public static final int LOCLEN

See Also:

Constant Field Values

LOCNAM

public static final int LOCNAM

See Also:

Constant Field Values

LOCEXT

public static final int LOCEXT

See Also:

Constant Field Values

EXTCRC

public static final int EXTCRC

See Also:

Constant Field Values

EXTSIZ

public static final int EXTSIZ

See Also:

Constant Field Values

EXTLEN

public static final int EXTLEN

See Also:

Constant Field Values

CENVEM

public static final int CENVEM

See Also:

Constant Field Values

CENVER

public static final int CENVER

See Also:

Constant Field Values

CENFLG

public static final int CENFLG

See Also:

Constant Field Values

CENHOW

public static final int CENHOW

See Also:

Constant Field Values

CENTIM

public static final int CENTIM

See Also:

Constant Field Values

CENCRC

public static final int CENCRC

See Also:

Constant Field Values

CENSIZ

public static final int CENSIZ

See Also:

Constant Field Values

CENLEN

public static final int CENLEN

See Also:

Constant Field Values

CENNAM

```
public static final int CENNAM
```

See Also:

Constant Field Values

CENEXT

```
public static final int CENEXT
```

See Also:

Constant Field Values

CENCOM

```
public static final int CENCOM
```

See Also:

Constant Field Values

CENDSK

```
public static final int CENDSK
```

See Also:

Constant Field Values

CENATT

```
public static final int CENATT
```

See Also:

Constant Field Values

CENATX

```
public static final int CENATX
```

See Also:

Constant Field Values

CENOFF

```
public static final int CENOFF
```

See Also:

Constant Field Values

ENDSUB

```
public static final int ENDSUB
```

See Also:

Constant Field Values

ENDTOT

```
public static final int ENDTOT
```

See Also:

Constant Field Values

ENDSIZ

```
public static final int ENDSIZ
```

See Also:

Constant Field Values

ENDOFF

```
public static final int ENDOFF
```

See Also:

Constant Field Values

ENDCOM

```
public static final int ENDCOM
```

See Also:

Constant Field Values

Constructor Detail

JarInputStream

```
public JarInputStream(InputStream in)
               throws IOException
```

Creates a new JarInputStream and reads the optional manifest. If a manifest is present, also attempts to verify the signatures if the JarInputStream is signed.

Parameters:

in - the actual input stream

Throws:

IOException - if an I/O error has occurred

JarInputStream

```
public JarInputStream(InputStream in,
                      boolean verify)
               throws IOException
```

Creates a new JarInputStream and reads the optional manifest. If a manifest is present and verify is true, also attempts to verify the signatures if the JarInputStream is signed.

Parameters:

in - the actual input stream

verify - whether or not to verify the JarInputStream if it is signed.

Throws:

IOException - if an I/O error has occurred

Method Detail

getManifest

```
public Manifest getManifest()
```

Returns the Manifest for this JAR file, or null if none.

Returns:

the Manifest for this JAR file, or null if none.

getNextEntry

```
public ZipEntry getNextEntry()
                       throws IOException
```

Reads the next ZIP file entry and positions the stream at the beginning of the entry data. If verification has been enabled, any invalid signature detected while positioning the stream for the next entry will result in an exception.

Overrides:

getNextEntry in class ZipInputStream

Returns:

the next ZIP file entry, or null if there are no more entries

Throws:

ZipException - if a ZIP file error has occurred

IOException - if an I/O error has occurred

SecurityException - if any of the jar file entries are incorrectly signed.

getNextJarEntry

```
public JarEntry getNextJarEntry()
                         throws IOException
```

Reads the next JAR file entry and positions the stream at the beginning of the entry data. If verification has been enabled, any invalid signature detected while positioning the stream for the next entry will result in an exception.

Returns:

the next JAR file entry, or null if there are no more entries

Throws:

ZipException - if a ZIP file error has occurred

IOException - if an I/O error has occurred

SecurityException - if any of the jar file entries are incorrectly signed.

read

```
public int read(byte[] b,
                int off,
                int len)
         throws IOException
```

Reads from the current JAR file entry into an array of bytes. If `len` is not zero, the method blocks until some input is available; otherwise, no bytes are read and `0` is returned. If verification has been enabled, any invalid signature on the current entry will be reported at some point before the end of the entry is reached.

Overrides:

`read` in class `ZipInputStream`

Parameters:

`b - the buffer into which the data is read`

`off - the start offset in the destination array b`

`len - the maximum number of bytes to read`

Returns:

`the actual number of bytes read, or -1 if the end of the entry is reached`

Throws:

`NullPointerException - If b is null.`

`IndexOutOfBoundsException - If off is negative, len is negative, or len is greater than b.length - off`

`ZipException - if a ZIP file error has occurred`

`IOException - if an I/O error has occurred`

`SecurityException - if any of the jar file entries are incorrectly signed.`

See Also:

`FilterInputStream.in`

createZipEntry

```
protected ZipEntry createZipEntry(String name)
```

Creates a new `JarEntry` (`ZipEntry`) for the specified JAR file entry name. The manifest attributes of the specified JAR file entry name will be copied to the new `JarEntry`.

Overrides:

createZipEntry in class ZipInputStream

Parameters:

name - the name of the JAR/ZIP file entry

Returns:

the JarEntry object just created

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.